

Σ SCiM 2026



BOOK OF ABSTRACTS

17th European Symposium on Computational
Intelligence and Mathematics
May 10th – 13th, 2026 • Timisoara, Romania

Editors:

László T. Kóczy, Jesús Medina

Associate Editors:

Roberto G. Aragón, Fernando Chacón-Gómez, Janusz Kacprzyk,

M. Eugenia Cornejo-Piñero, David Lobo, Francisco J. Ocaña-Alcázar, Eloísa Ramírez-Poussa

Book of abstracts of ESCIM 2026

© László T. Kóczy, Jesús Medina, Editors
Roberto G. Aragón, Fernando Chacón-Gómez, María Eugenia Cornejo,
Janusz Kacprzyk, David Lobo, Francisco J. Ocaña-Alcázar,
Eloísa Ramírez-Poussa, Associate Editors

Edition 1st
First published: 2026

ISBN: XXX-XX-XX-XXXXX-X
Published and printed by:
Universidad de Cádiz (Dept. Matemáticas), Spain.

Table of Contents

Keynote: A Personality and Emotional Disregulation-based Decision system for categorizing online gambling addiction levels	1
<i>Yiyu Yao</i>	
A Personality and Emotional Disregulation-based Decision system for categorizing online gambling addiction levels	2
<i>Jesús Serrano-Guerrero, Woorod Al-Muhtaseb, Abdullah Abdulgafer, Guadalupe Plaza, Andrés Montoro-Montarroso, Francisco P. Romero and José A. Olivas</i>	
Benchmarking Metaheuristic Algorithms for Revenue-Driven Timetabling in Deregulated Railway Markets	4
<i>David Muñoz-Valero, Juan Moreno-García, Julio Alberto López-Gómez and Enrique Adrián Villarrubia-Martín</i>	
Fairness-Aware Optimization for Train Timetabling in Liberalized Railway Markets: A Comparative Study of Equity Metrics	6
<i>David Muñoz-Valero, Juan Moreno-García, Julio Alberto López-Gómez and Enrique Adrián Villarrubia-Martín</i>	
Deconvolutional Networks as an XAI Method for Convolutional Neural Networks in Brain MRI Classification	8
<i>Piotr Kowalski</i>	
A Scenario-Based Fuzzy Cognitive Map Approach to ESG Analysis in Higher Education	10
<i>József Hegedüs, László T. Kóczy and Miklós F. Hatwagner</i>	
Fuzzy Cognitiv Map Modell reduction with Neural Network	12
<i>Barbara Sebestyén, Miklós F. Hatwagner and László T. Kóczy</i>	
Keynote: Harnessing AI with Limited Data: Approximate Knowledge Interpolation and Practical Applications	14
<i>Qiang Shen</i>	
From fuzzy measures to communities: a clustering approach for interpretation	15
<i>Carlos I. Pérez-Sechi, Inmaculada Gutiérrez, Javier Castro and Daniel Gómez</i>	
Formal Concept Analysis for Evaluating the Intent Dimension of LLMs . .	17
<i>Adam Leiyi Chen-Abolacio and Joaquín Borrego-Díaz</i>	
On the aggregation of contexts with common attributes	19
<i>Roberto G. Aragón, Jesús Medina and Samuel Molina-Ruiz</i>	

Interactive Fuzzy FCA Recommender System: A Visual Approach using fcaR	21
<i>Ángel Mora Bonilla, Domingo López-Rodríguez and Manuel Ojeda-Hernández</i>	
Definition and resolution of bipolar multi-adjoint relation equations	23
<i>M. Eugenia Cornejo, David Lobo and Jesús Medina</i>	
Characterizing the solvability of bipolar sup-equations in terms of the negation operator	24
<i>David Lobo, Pablo López-Molina</i>	
Keynote: Model-based and Data-driven Low-cost Fuzzy Controllers with Servo System Applications	26
<i>Radu-Emil Precup</i>	
Optimizing Hierarchical Fuzzy Signatures for Masonry Compressive Strength Assessment	27
<i>András Kaszás, Vanda O. Pomezanski and László T. Kóczy</i>	
Applying The Fuzzy Signatures Concepts for Linguistic Values	29
<i>Nour Ammar and László T. Kóczy</i>	
A First Exploration of Concept Representation in Latent Space	31
<i>Arturo Fernández-Mora, Juan Moreno-García, David Muñoz-Valero and Luis Martínez</i>	
Application of Intermediate Quantifiers Forming a Logical Structure of Opposition	34
<i>Vilém Novák, Petra Murinova and Karel Fiala</i>	
Standard completeness of multi-adjoint Gödel logic	36
<i>M. Eugenia Cornejo, Francesc Esteva, Luis Fariñas del Cerro, Lluis Godo and Jesús Medina</i>	
From ASP to L-DINF: Towards Epistemic Dietary Agents for Personalized Nutrition	38
<i>Stefania Costantini, Valentina Pitoni and Alina Vozna</i>	
Hybrid cd-implications to handle mixed information	40
<i>Fernando Chacón-Gómez, M. Eugenia Cornejo and Jesús Medina</i>	
Towards the non recursive notion of pseudo-intent in residuated concept lattices with hedges	42
<i>M. Eugenia Cornejo, Jesús Medina and Francisco J. Ocaña-Alcázar</i>	

A hybrid framework for integrating three-valued and fuzzy Formal Concept Analysis	44
<i>Manuel Enciso, Pablo Cordero, Ángel Mora and Francisco Pérez- Gámez,</i>	
Keynote: Fuzzy Models in Anytime Systems	46
<i>Annamária R. Várkonyi-Kóczy</i>	
Difference between divisibility and smoothness for pseudo-t-norms on finite lattices	47
<i>Juraj Kalafut, Martin Kalina, Ivona Hrivová and Andrea Mesiarová- Zeménková</i>	
Codomain lattice and optimization problems	49
<i>Vanja Stepanović and Andreja Tepavčević</i>	
Omega-algebras in classical fuzzy setting	51
<i>Vanja Stepanović, Andreja Tepavčević and Aleksandar Trkulja</i>	
Fairness Distortion Index: A Fuzzy Aggregation Framework for Evaluating League Scheduling Bias	53
<i>Boldizsár Tüű-Szabó and László T. Kóczy</i>	
From Voting to Aggregation: An Aggregation-Based Interpretation of Alternative Voting Mechanisms in the Fuzzy Hough Transform	55
<i>Szilvia Nagy and Brigita Sziová</i>	
On aggregation of T_M -fuzzy vector subspaces	57
<i>Dragan Jočić and Ivana Štajner-Papuga</i>	
On discrete Sugeno integral and aggregation of algebraic objects	59
<i>Ivana Štajner-Papuga and Andreja Tepavčević</i>	

Program Committee

María José Benítez-Caballero	University of Cádiz. Spain
Pedro Cabalar	Univ. A Coruña. Spain
João Paulo Carvalho	University of Lisbon. Portugal
Oscar Castillo	Tijuana Institute of Technology. México
Ciprian-Bogdan Chirila	Politehnica University of Timisoara. Romania
Agata Ciabattoni	TU Wien. Austria
Davide Ciucci	University of Milano-Bicocca. Italy
M. Eugenia Cornejo	University of Cádiz, Spain
Chris Cornelis	University of Gante. Belgium
Stefania Costantini	University of L'Aquila. Italy
Bernard De Baets	University of Gante. Belgium
Christian G. Fermüller	TU Wien. Austria
Péter Földesi	Univ. Széchenyi István. Hungary
Robert Fullér	Obuda University, Hungary
Lluís Godo	Artificial Intelligence Research Institute, IIIA-CSIC. Spain
István Á. Harmati	Univ. Széchenyi István. Hungary
Piotr A. Kowalski	AGH Univ. of Science and Technology. Poland
Stanislav Krajčí	UPJS Košice. Slovakia
Ondrej Krídlo	UPJS Košice. Slovakia
David Lobo	University of Cádiz. Spain
Nicolás Madrid	University of Cádiz. Spain
Viviana Mascardi	University of Genova. Italy
Juan Moreno García	University of Castilla La Mancha. Spain
Szilvia Nagy	Univ. Széchenyi István. Hungary
Manuel Ojeda-Aciego	University of Málaga. Spain
Irina Perfilieva	Centre of Excellence IT4Innovations. Univ. Ostrava. Czech Republic
Jozef Pócs	Slovak Academy of Sciences. Slovakia
Claudiu Pozna	Transilvania University of Brasov. Romania
Radu-Emil Precup	Politehnica University of Timisoara. Rumania
Marek Reformat	University of Alberta. Canada
Eloísa Ramírez-Poussa	University of Cádiz. Spain
Andreja Tepavčević	University of Novi Sad. Serbia
Esko Turunen	Tampere University of Technology. Finland

Program of the
17th European Symposium
on Computational Intelligence and Mathematics
May 10th - 13th, 2026. Timisoara, Romania



MONDAY 11 th	
Location: Continental Hotel	
8:30	Open Registration Desk
9:00–9:30	Inauguration
9:30–10:30	Keynote Speaker - Yiyu Yao Title: Three-way decision: A computational intelligence perspective Chairperson: Jesús Medina
10:30–11:00	Coffee break
11:00–12:00	Special Session: Decision and optimization model applied to logistics and transport Chairperson: Julio Alberto López-Gómez
	<i>A Personality and Emotional Disregulation-based Decision system for categorizing online gambling addiction levels</i> Jesús Serrano-Guerrero, Woorod Al-Muhtaseb, Abdullah Abdulgafer, Guadalupe Plaza, Andrés Montoro-Montarroso, Francisco Romero, José A. Olivas
	<i>Benchmarking Metaheuristic Algorithms for Revenue-Driven Timetabling in Deregulated Railway Markets</i> David Muñoz-Valero, Juan Moreno-García, Julio Alberto López-Gómez, Enrique Adrián Villarrubia-Martín
	<i>Fairness-Aware Optimization for Train Timetabling in Liberalized Railway Markets: A Comparative Study of Equity Metrics</i> David Muñoz-Valero, Juan Moreno-García, Julio Alberto López-Gómez, Enrique Adrián Villarrubia-Martín
12:00–12:10	Break
12:10–13:10	Regular Session 1 Chairperson: Szilvia Nagy & Boldizsár Tüü-Szabó
	<i>Deconvolutional Networks as an XAI Method for Convolutional Neural Networks in Brain MRI Classification</i> Piotr Kowalski
	<i>A Scenario-Based Fuzzy Cognitive Map Approach to ESG Analysis in Higher Education</i> József Hegedüs, László T. Kóczy, Miklós Hatwagner
	<i>Fuzzy Cognitive Map Modell reduction with Neural Network</i> Barbara Sebestyén, László T. Kóczy, Miklós F. Hatwagner
13:10–15:00	Lunch

15:00–16:00	Keynote Speaker - Qiang Shen Title: Harnessing AI with Limited Data: Approximate Knowledge Interpolation and Practical Applications Chairperson: László T. Kóczy
16:00–16:20	Coffee break
16:20–18:20	Special Session: Recent trends in knowledge representation and modelling. Part 1 Chairperson: Ivana Štajner-Papuga
	<i>From fuzzy measures to communities: a clustering approach for interpretation</i> Inmaculada Gutiérrez García-Pardo, Carlos I. Pérez-Sechi, Javier Castro, Daniel Gómez
	<i>Formal Concept Analysis for Evaluating the Intent Dimension of LLMs</i> Adam Leiyi Chen, Joaquín Borrego
	<i>On the aggregation of contexts with common attributes</i> Roberto G. Aragón, Jesús Medina, Samuel Molina-Ruiz
	<i>Interactive Fuzzy FCA Recommender System: A Visual Approach using fcaR</i> Ángel Mora Bonilla, Domingo López-Rodríguez, Manuel Ojeda-Hernández
	<i>Definition and resolution of bipolar multi-adjoint relation equations</i> M. Eugenia Cornejo, David Lobo, Jesús Medina
	<i>Characterizing the solvability of bipolar sup-equations in terms of the negation operator</i> David Lobo, Pablo López-Molina
20:00	Welcome reception

TUESDAY 12th	
Location: Continental Hotel	
9:00–10:00	Keynote Speaker - Radu-Emul Precup Title: Model-based and Data-driven Low-cost Fuzzy Controllers with Servo System Applications Chairperson: Andreja Tepavčević
10:00–11:00	Regular Session 2 Chairperson: Vilém Novák
	<i>Optimizing Hierarchical Fuzzy Signatures for Masonry Compressive Strength Assessment</i> András Kaszás, Vanda O. Pomezanski, László T. Kóczy
	<i>Applying The Fuzzy Signatures Concepts for Linguistic Values</i> Nour Ammar, László T. Kóczy
	<i>A First Exploration of Concept Representation in Latent Space</i> Arturo Fernández-Mora, Juan Moreno-García, David Muñoz-Valero, Luis Martínez
11:00–11:30	Coffee break
11:30–13:30	Special Session: Recent trends in knowledge representation and modelling. Part 2 Chairperson: David Lobo
	<i>Application of Intermediate Quantifiers Forming a Logical Structure of Opposition</i> Vilém Novák, Petra Murinova, Karel Fiala
	<i>Real-valued semantics for the Multi-adjoint Gödel logic</i> María Eugenia Cornejo, Francesc Esteva, Luis Fariñas-del Cerro, Lluís Godo, Jesús Medina
	<i>From Answer Set Programming to Epistemic Agents: A Hybrid Framework for Personalized Nutrition</i> Alina Vozna, Stefania Costantini, Valentina Pitoni
	<i>Hybrid cd-implications to handle mixed information</i> Fernando Chacón-Gómez, M. Eugenia Cornejo, Jesús Medina
	<i>Towards the non recursive notion of pseudo-intent in residuated concept lattices with hedges</i> M. Eugenia Cornejo, Jesús Medina, Francisco J. Ocaña-Alcázar
	<i>A hybrid framework for integrating three-valued and fuzzy Formal Concept Analysis</i> Francisco Pérez-Gámez, Pablo Cordero, Manuel Enciso, Ángel Mora
13:30–15:30	Lunch
15:30–17:30	Timisoara tour
20:30	Gala dinner

WEDNESDAY 13th	
Location: Continental Hotel	
10:00–10:50	Keynote Speaker - Annamária R. Várkonyi-Kóczy Title: Fuzzy Models in Anytime Systems Chairperson: Manuel Ojeda-Aciego
10:50–11:10	Coffee break
11:10–12:10	Regular Session 3 Chairperson: Martin Kalina
	<i>Difference between divisibility and smoothness for pseudo-t-norms on finite lattices</i> Juraj Kalafut, Martin Kalina, Ivona Hrivová, Andrea Mesiarová-Zeménková
	<i>Codomain lattice and optimization problems</i> Vanja Stepanović, Andreja Tepavčević
	<i>Omega-algebras in classical fuzzy setting</i> Vanja Stepanović, Andreja Tepavčević, Aleksandar Trkulja
12:10–13:30	Regular Session 4 Chairperson: Pablo Cordero
	<i>Fairness Distortion Index: A Fuzzy Aggregation Framework for Evaluating League Scheduling Bias</i> Boldizsár Tüü-Szabó, László T. Kóczy
	<i>From Voting to Aggregation: An Aggregation-Based Interpretation of Alternative Voting Mechanisms in the Fuzzy Hough Transform</i> Szilvia Nagy, Brigita Sziová
	<i>On aggregation of T_M-fuzzy vector subspaces</i> Dragan Jočić, Ivana Štajner-Papuga
	<i>On discrete Sugeno integral and aggregation of algebraic objects</i> Ivana Štajner-Papuga, Andreja Tepavčević
13:30–15:50	Closing Session – Lunch

Social Events

SUNDAY 10th

08:30 **Tour to Arad and Balla Geza Winehouse, Minis**

MONDAY 11th

20:00 **Welcome reception**

TUESDAY 12th

15:30–17:30 **Timisoara tour**

20:30 **Gala dinner**

WEDNESDAY 13th

13:30–15:30 **Closing Session**

Keynote speech:

Three-way decision: A computational intelligence perspective

Yiyu Yao

Department of Computer Science,
University of Regina, Canada.



Abstract: A theory of three-way decision is about thinking in threes, problem solving in threes, and computing in threes. This talk covers the principles, methods, and applications of three-way decision from a computational intelligence perspective. The three parts of the talk are (a) basics of three-way decision, (b) thinking in threes in computational intelligence and mathematics, and (c) implications of three-way decision to computational intelligence.

A Personality and Emotional Disregulation-based Decision system for categorizing online gambling addiction levels

Jesús Serrano-Guerrero¹, Woorod Al-Muhtaseb^{1,2}, Abdullah Abdulgafer^{1,2}, Guadalupe Plaza¹, Andrés Montoro-Montarroso¹, Francisco P. Romero¹ and José A. Olivas¹

¹ University of Castilla-La Mancha, Escuela Superior de Informatica, Paseo de la Universidad 4, 13071, Ciudad Real, Spain

e-mail: {jesus.serrano, guadalupe.plaza, andres.montoro, jared.guerrero, franciscop.romero, joseangel.olivas}@uclm.es

² Faculty of Information Technology, Applied Science Private University, Amman, Jordan

e-mail: {w_muhtaseb,a_abdalgafer}@asu.edu.jo

Abstract: Gambling disorder remains largely undetected due to a significant “help-seeking gap.” This study proposes a scalable decision system for early detection by monitoring social media narratives. By leveraging Large Language Models and ontologies, the system identifies “digital fingerprints” of personality (UPPS-P) and emotional dysregulation-key factors where gambling serves as “emotional self-medication.” The architecture transforms unstructured discourse into clinical indicators, integrating impulsivity facets and affective states to generate early warnings. This approach represents a vital step toward proactive, personalized prevention in behavioral addictions.

Keywords: Gambling disorder · Impulsivity · Emotional dysregulation · Large Language Models · Social media

Acknowledgement: This study has been supported by the Spanish Ministry of Social Rights, Consumption and Agenda 2030 under the project Detec-EMO 2.0 (SUBV24/00018).

References

1. Smith, E., Peters, J., and Reiter, N. (2024). Automatic detection of problem gambling signs from online texts using large language models, *PLOS Digital Health* 3(9), e0000605. <https://doi.org/10.1371/journal.pdig.0000605>.
2. Connecticut Department of Mental Health and Addiction Services. (2013). DSM-5 Diagnostic Criteria: Gambling Disorder. <https://portal.ct.gov/-/media/dmhas/pgs/dsmdiagnosispdf.pdf> (Accessed: 2025-11-22).

3. Lesieur, H. R., and Blume, S. B. (1987). The South Oaks Gambling Screen (SOGS): a new instrument for the identification of pathological gamblers, *The American Journal of Psychiatry*.
4. Miller, N. V., Currie, S. R., Hodgins, D. C., and Casey, D. (2013). Validation of the problem gambling severity index using confirmatory factor analysis and rasch modelling, *International Journal of Methods in Psychiatric Research* 22(3), 245–255.
5. González-Cabrera, J., Machimbarrena, J. M., Beranuy, M., Pérez-Rodríguez, P., Fernández-González, L., and Calvete, E. (2020). Design and measurement properties of the Online Gambling Disorder Questionnaire (OGD-Q) in Spanish adolescents, *Journal of Clinical Medicine*.
6. Whiteside, S. P., and Lynam, D. R. (2001). The Five Factor Model and impulsivity: Using a structural model of personality to understand impulsivity, *Personality and Individual Differences* 30, 669-689.
7. Lynam, D. R., Smith, G. T., Whiteside, S. P., and Cyders, M. A. (2006). The UPPSP: Assessing five personality pathways to impulsive behavior (Technical Report). West Lafayette, IN: Purdue University.
8. Jiang, A. Q., Sablayrolles, A., Mensch, A., Bamford, C., Chaplot, D. S., de las Casas, D., Bressand, F., Lengyel, G., Lample, G., Saulnier, L., Lavaud, L. R., Lachaux, M.-A., Stock, P., Le Scao, T., Lavril, T., Wang, T., Lacroix, T., and El Sayed, W. (2023). Mistral 7B, *arXiv preprint arXiv:2310.06825*. <https://arxiv.org/abs/2310.06825>.
9. Marionneau, V., and Nikkinen, J. (2022). Gambling-related suicides and suicidality: a systematic review of qualitative evidence, *Frontiers in Psychiatry* 13, 980303.
10. Bijker, R., Booth, N., Merkouris, S. S., Dowling, N. A., and Rodda, S. N. (2022). Global prevalence of help-seeking for problem gambling: a systematic review and meta-analysis, *Addiction* 117(12), 2972–2985.
11. Tran, L. T., et al. (2024). The prevalence of gambling and problematic gambling: a systematic review and meta-analysis, *The Lancet Public Health*.
12. Bucur, A.-M., Cosma, A., and Dinu, L. P. (2021). Early Risk Detection of Pathological Gambling, Self-Harm and Depression Using BERT, *CEUR Workshop Proceedings* 2936.
13. Cohan, A., et al. (2018). SMHD: a Large-Scale Resource for Exploring Online Language Usage for Multiple Mental Health Conditions. *COLING 2018*, 1485–1497.
14. Garg, M. (2023). Mental health analysis in social media posts: a survey, *Archives of Computational Methods in Engineering* 30(3), 1819.
15. Álvarez-Ojeda, P., et al. (2025). The PRECOM-SM Corpus: Gambling in Spanish Social Media. *COLING 2025*, 17–28.
16. Alshouha, B., Serrano-Guerrero, J., Chiclana, F., Romero, F. P., and Olivas, J. A. (2024). Personality Trait Detection via Transfer Learning, *Computers, Materials & Continua* 78(2), 1933–1956. doi: 10.32604/cmc.2023.046711.
17. Serrano-Guerrero, J., Alshouha, B., Bani-Doumi, M., Chiclana, F., Romero, F. P., and Olivas, J. A. (2024). Combining machine learning algorithms for personality trait prediction, *Egyptian Informatics Journal* 25, 100439. doi: 10.1016/j.eij.2024.100439.

Benchmarking Metaheuristic Algorithms for Revenue-Driven Timetabling in Deregulated Railway Markets

David Muñoz-Valero¹, Juan Moreno-García¹, Julio Alberto López-Gómez² and Enrique Adrián Villarrubia-Martín²

¹ Escuela de Ingeniería Industrial y Aeroespacial de Toledo, Department of Technologies and Information Systems, Universidad de Castilla-La Mancha, Avenida Carlos III, s/n, Toledo, 45071, Spain

e-mail: {david.munoz,juan.moreno}@uclm.es

² Escuela Superior de Informática, Department of Technologies and Information Systems, Universidad de Castilla-La Mancha, Paseo de la Universidad 4, Ciudad Real, 13071, Spain

e-mail: {julioalberto.lopez,enrique.villarrubia}@uclm.es

Abstract: The liberalization of the European railway sector requires new approaches to coordinate the commercial interests of Railway Undertakings (RUs) with the capacity management objectives of Infrastructure Managers (IM) [1]. This contribution presents a summary of the work originally published in [2], which addresses the Train Timetabling Problem (TTP) in a deregulated market. The original study formulates the TTP as an optimization problem aimed at maximizing IM revenue while minimizing penalties derived from deviations in RUs' requested schedules. This work outlines the modular simulation framework presented in [2] to evaluate the performance of ten different metaheuristic algorithms—including Genetic Algorithms (GA), Particle Swarm Optimization (PSO), and Differential Evolution (DE)—implemented via the MEALPY library [3]. Furthermore, the scalability of these approaches is analyzed by comparing them against the SCIP exact mathematical solver [4] modeled in Pyomo [5]. Experimental results indicate that while exact methods struggle with scalability in large instances (e.g., 50 service requests), the Genetic Algorithm consistently delivers superior performance in terms of revenue maximization, convergence speed, and schedule adherence. The study concludes that properly tuned metaheuristics offer a robust and efficient solution for tactical planning in competitive railway environments.

Keywords: Railway Timetabling · Metaheuristics · Deregulated Market · Genetic Algorithm · Optimization

Acknowledgement: This work was supported by grants PID2020-112967GB-C32 and PID2020-112967GB-C33 funded by MCIN/AEI/10.13039/501100011033, by ERDF A Way of Making Europe and the Research Vice-Rectorry of the Universidad de Castilla-La Mancha. It was completed when Enrique Adrian

Villarrubia- Martin was a predoctoral fellow at the Universidad de Castilla-La Mancha funded by the European Social Fund Plus (ESF+).

References

1. Ait-Ali, A., Eliasson, J. European railway deregulation: an overview of market organization and capacity allocation, *Transportmetrica A: Transport Science* 18, 594–618, 2021.
2. Muñoz-Valero, D., Moreno-Garcia, J., López-Gómez, J. A., Villarrubia-Martin, E. A., Rodriguez-Benitez, L. An approach to the timetabling problem in deregulated railway markets based on metaheuristic algorithms, *Integrated Computer-Aided Engineering* 0 (0) 10692509251392410. URL: <https://doi.org/10.1177/10692509251392410>. doi:10.1177/10692509251392410.
3. Thieu, N. V., Mirjalili, S. Mealy: An open-source library for latest meta-heuristic algorithms in python, *Journal of Systems Architecture* 139, 2023.
4. Achterberg, T. Scip: solving constraint integer programs, *Mathematical Programming Computation* 1, 1–41, 2009. URL: <https://doi.org/10.1007/s12532-008-0001-1>doi:10.1007/s12532-008-0001-1.
5. Hart, W. E., Watson, J.-P., Woodruff, D. L. Pyomo: modeling and solving mathematical programs in python, *Mathematical Programming Computation* 3, 219–260, 2011.

Fairness-Aware Optimization for Train Timetabling in Liberalized Railway Markets: A Comparative Study of Equity Metrics

David Muñoz-Valero¹, Juan Moreno-García¹, Julio Alberto López-Gómez² and Enrique Adrián Villarrubia-Martín²

¹ Escuela de Ingeniería Industrial y Aeroespacial de Toledo, Department of Technologies and Information Systems, Universidad de Castilla-La Mancha, Avenida Carlos III, s/n, Toledo, 45071, Spain

e-mail: {david.munoz,juan.moreno}@uclm.es

² Escuela Superior de Informática, Department of Technologies and Information Systems, Universidad de Castilla-La Mancha, Paseo de la Universidad 4, Ciudad Real, 13071, Spain

e-mail: {julioalberto.lopez,enrique.villarrubia}@uclm.es

Abstract: The liberalization of the European railway sector has introduced competition among Railway Undertakings (RUs) for limited infrastructure capacity, challenging Infrastructure Managers (IM) to allocate slots not only efficiently but also equitably. This contribution summarizes the research currently under review in [1], which proposes a fairness-oriented timetabling framework. Unlike traditional approaches that prioritize IM revenue—often leading to monopolistic behaviors—the proposed methodology integrates equity metrics such as the Jain index [2], Gini coefficient [3], and Atkinson index [4] into the optimization process. A Genetic Algorithm is employed, implemented via the MEALPY library [5] coupled with a conflict resolution heuristic designed to protect the most disadvantaged operators. Experimental results, simulated on a high-speed corridor using the ROBIN simulator [6], demonstrate that incorporating these metrics significantly reduces allocation inequity across different competitiveness scenarios. The study highlights a quantifiable trade-off between maximizing revenue and ensuring fair market access, supporting the use of these equity indices as decision-support tools for sustainable railway ecosystems.

Keywords: Railway Timetabling · Fairness · Liberalized Market · Equity Metrics · Genetic Algorithm.

Acknowledgement: This work was supported by grants PID2020-112967GB-C32 and PID2020-112967GB-C33 funded by MCIN/AEI/10.13039/501100011033, by ERDF A Way of Making Europe and the Research Vice-Rector of the Universidad de Castilla-La Mancha. It was completed when Enrique Adrian Villarrubia- Martin was a predoctoral fellow at the Universidad de Castilla-La Mancha funded by the European Social Fund Plus (ESF+).

References

1. Muñoz-Valero, D., et al. Towards equitable rail service allocation through fairness-oriented timetabling in liberalized markets, *Computers & Industrial Engineering*, 2025. Under Review.
2. Jain, R. K., Chiu, D.-M. W., Hawe, W. R. A quantitative measure of fairness and discrimination, Eastern Research Laboratory, Digital Equipment Corporation, Hudson, MA 21, 1984.
3. Gini, C. Variabilità e mutabilità: contributo allo studio delle distribuzioni e delle relazioni statistiche. [Fasc. I.], Tipogr. di P. Cuppini, 1912.
4. Atkinson, A. B. On the measurement of inequality, *Journal of economic theory* 2, 244–263, 1970.
5. Van Thieu, N., Mirjalili, S. MEALPY: An open-source library for latest meta-heuristic algorithms in Python, *Journal of Systems Architecture* 139, 2023. doi:10.1016/j.sysarc.2023.102871.
6. del Castillo-Herrera, E., García-Ródenas, R., Jimenez-Linares, L., López-García, M. L., López-Gómez, J. A., Martín-Baos, J. A., Moreno-García, J., Muñoz-Valero, D., Rodríguez-Benitez, L., Villarrubia-Martin, E. A. ROBIN: Rail mOBility simulatioN, in: *Transportation Research Procedia*, volume 78, Elsevier B.V., pp. 158–165, 2024. doi:10.1016/j.trpro.2024.02.021.

Deconvolutional Networks as an XAI Method for Convolutional Neural Networks in Brain MRI Classification

Piotr Kowalski

¹ Faculty of Physics and Applied Computer Science, AGH University of Krakow, al. A. Mickiewicza 30, 30-059 Krakow, Poland.

e-mail: pkowal@agh.edu.pl

² Systems Research Institute, Polish Academy of Sciences, ul. Newelska 6, 01-447 Warsaw, Poland.

Abstract: In medical applications, achieving high predictive performance is necessary but not sufficient; the rationale behind a model’s decisions must also be assessable. Convolutional neural networks (CNNs) can deliver strong results in magnetic resonance imaging (MRI) analysis, yet their decision-making process is difficult to interpret. This article presents deconvolutional networks as a local explanation method for individual CNN predictions. The core mechanism is reviewed, including the backward projection of activations from feature space to the input domain via unpooling and transposed convolutions. The method is discussed in a four-class brain MRI classification setting, comparing a shallow custom CNN with a transfer-learned VGG19 model. Numerical performance (94.69% and 97.73% test accuracy, respectively) is complemented by qualitative observations derived from deconvolutional visualisations and their relation to perturbation-based explanations. The analysis highlights practical benefits of deconvolutional views for sanity-checking spatial focus, as well as limitations in multi-class settings and in deeper reconstructions for transfer-learned models.

Keywords: deconvolutional networks · explainable AI (XAI) · activation map visualisation · transposed convolution · unpooling · CNN · brain MRI analysis.

Acknowledgement: This work was partially supported by Grant for Statutory Activity from the Faculty of Physics and Applied Computer Science of the AGH University of Krakow. Parts of this research were conducted in collaboration with Łukasz Jarosz, concurrent with his thesis work.

References

1. Jeczminek, E., Kowalski, P.A.: Input reduction of convolutional neural networks with global sensitivity analysis as a data-centric approach. *Neurocomputing* **506**, 196–205 (2022). <https://doi.org/https://doi.org/10.1016/j.neucom.2022.07.027>, <https://www.sciencedirect.com/science/article/pii/S0925231222008888>

2. Jeczminek, E., Kowalski, P.A.: P-norm choice for high level classification features pruning in modern convolutional neural networks with local sensitivity analysis. *International Journal of Applied Mathematics and Computer Science* (2023)
3. Kowalski, P.A., Kusy, M.: Sensitivity analysis for probabilistic neural network structure reduction. *IEEE Transactions on Neural Networks and Learning Systems* **29**(5), 1919–1932 (2018). <https://doi.org/10.1109/TNNLS.2017.2688482>
4. Kshatri, S.S., Singh, D.: Convolutional neural network in medical image analysis: a review. *Archives of Computational Methods in Engineering* **30**(4), 2793–2810 (2023)
5. Kusy, M., Kowalski, P.A.: Modification of the probabilistic neural network with the use of sensitivity analysis procedure. In: 2016 Federated Conference on Computer Science and Information Systems (FedCSIS). pp. 97–103. IEEE (2016)
6. Kusy, M., Szwagrzyk, M., Kowalski, P.A., Konior, A.: Machine learning techniques for explaining air pollution prediction. In: The IEEE World Congress on Computational Intelligence (IEEE WCCI), International Joint Conference on Neural Networks (IJCNN-IEEE 2022). pp. 1–8. Padova (Italy) (07 2022). <https://doi.org/10.1109/IJCNN55064.2022.9891994>
7. Nickparvar, M.: Brain tumor mri dataset (2021). <https://doi.org/10.34740/KAGGLE/DSV/2645886>, <https://www.kaggle.com/dsv/2645886>
8. Noh, H., Hong, S., Han, B.: Learning deconvolution network for semantic segmentation. In: Proceedings of the IEEE International Conference on Computer Vision (ICCV) (December 2015)
9. Qin, Z., Yu, F., Liu, C., Chen, X.: How convolutional neural network see the world - a survey of convolutional neural network visualization methods (2018), <https://arxiv.org/abs/1804.11191>
10. Tsuneki, M.: Deep learning models in medical image analysis. *Journal of Oral Biosciences* **64**(3), 312–320 (2022)
11. Zeiler, M.D., Krishnan, D., Taylor, G.W., Fergus, R.: Deconvolutional networks. In: 2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition. pp. 2528–2535 (2010). <https://doi.org/10.1109/CVPR.2010.5539957>

A Scenario-Based Fuzzy Cognitive Map Approach to ESG Analysis in Higher Education

József Hegedüs¹, László T. Kóczy² and Miklós F. Hatwagner²

¹ University of Pécs, Pécs, Hungary

e-mail: hegedus.jozsef@mik.pte.hu

² Széchenyi István University, Győr, Hungary

e-mail: {koczy,miklos.hatwagner}@sze.hu

Abstract: This paper presents a scenario-based modeling framework using fuzzy cognitive maps (FCMs) for analyzing the interactions among environmental, social, and governance (ESG) dimensions in higher education systems. In the proposed model, key ESG areas are represented as interconnected concepts whose relationships are described through a weighted cognitive map. The dynamic behavior of the system is examined through an iterative update mechanism combined with a sigmoid activation function, allowing causal influences to propagate across the network.

Scenario analysis is conducted by applying moderate perturbations to selected ESG components and simulating the resulting system dynamics. The simulations reveal that the modeled system consistently converges to a stable equilibrium state across all examined scenarios. Although targeted interventions produce measurable short-term deviations during the transient phase, the long-term system behavior remains unchanged.

These results indicate the presence of a dominant attractor in the modeled system and suggest structural stability with respect to moderate perturbations. The study highlights the usefulness of fuzzy cognitive maps as an exploratory modeling and decision-support tool for analyzing complex interdependencies and dynamic responses in ESG-oriented higher education systems.

Keywords: ESG assessment · higher education · fuzzy cognitive maps · scenario analysis · system dynamics · sustainability

References

1. Bakhtavar, E., Valipour, A., Tamošaitienė, J. Fuzzy cognitive maps in systems risk analysis: A comprehensive review, *Complex Intell. Syst.* 7, 621–637 (2021)
2. Berg, F., Kölbl, J., Rigobon, R. Aggregate confusion: The divergence of ESG ratings, *Rev. Finance* 26(6), 1315–1344 (2022)
3. European Association for Quality Assurance in Higher Education (ENQA). Standards and Guidelines for Quality Assurance in the European Higher Education Area (ESG), 2nd edn. ENQA, Brussels (2015)

4. Friede, G., Busch, T., Bassen, A. ESG and financial performance: Aggregated evidence from more than 2000 empirical studies, *J. Sustain. Finance Invest.* 5(4), 210–233 (2015)
5. Jing, X. Exploration of an innovative model of higher education management and student training mechanism based on cognitive mapping, *Appl. Math. Nonlinear Sci.* 9(1) (2024)
6. Kakulia, N., Tvalodze, S. Determinants of ESG sustainability in financial systems: A fuzzy cognitive approach with a focus on Georgia, *Entrep. Sustain. Issues* 12(3), 10–21 (2025)
7. Kosko, B. Fuzzy cognitive maps, *Int. J. Man-Mach. Stud.* 24(1), 65–75 (1986)
8. Kotsantonis, S., Serafeim, G. Four things no one will tell you about ESG data, *J. Appl. Corp. Finance* 31(2), 50–58 (2019)
9. Papageorgiou, E.I., Salmeron, J.L. A review of fuzzy cognitive map research during the last decade, *IEEE Trans. Fuzzy Syst.* 21(1), 66–79 (2013)
10. Sterman, J.D. *Business Dynamics: Systems Thinking and Modeling for a Complex World*, McGraw-Hill, Boston (2000)

Fuzzy Cognitive Map Model reduction with Neural Network

Barbara Sebestyén, Miklós F. Hatwagner and László T. Kóczy

Dept. of Information Technology, Széchenyi István University, Győr, Hungary

e-mail: barbara.sebestyen.10@gmail.com, miklos.hatwagner@sze.hu, koczy@sze.hu

Abstract: This paper presents a behavior-preserving reduction method for Fuzzy Cognitive Maps (FCMs) based on a modified Multilayer Perceptron (MLP). Instead of learning static input-output mappings, the proposed approach focuses on preserving the dynamic behavior of the original system during the reduction process. The quality of the reduction is evaluated by comparing output concept trajectories over multiple update steps using the Mean Absolute Error (MAE). The results show that the essential dynamics of the original FCM can be preserved across different reduction levels with low computational cost.

Keywords: Fuzzy Cognitive Maps · Reduction · Multilayer Perceptron

References

1. Hatwagner, M.F., Buruzs, A., Földesi, P., Kóczy, L.T. A new state reduction approach for fuzzy cognitive maps with case studies for waste management systems. In: Computational Intelligence in Information Systems. Advances in Intelligent Systems and Computing, vol. 331, pp. 119–127. Springer (2015) https://doi.org/10.1007/978-3-319-13153-5_12
2. Hatwagner, M.F., Yesil, E., Dodurka, M.F., Papageorgiou, E.I., Urbas, L., Kóczy, L.T. Two-stage learning based fuzzy cognitive maps reduction approach, *IEEE Transactions on Fuzzy Systems* **26**(5), 2938–2952 (2018) <https://doi.org/10.1109/TFUZZ.2018.2793904>
3. Hosseini, S., et al. Fuzzy cognitive map for evaluating critical factors causing rockburst in underground excavations, *Rock Mechanics and Rock Engineering* (2024)
4. Karatzinis, G.D., Boutalis, Y.S. A review study of fuzzy cognitive maps in engineering: Applications, insights, and future directions, *Eng* **6**(2), 37 (2025) <https://doi.org/10.3390/eng6020037>
5. LeCun, Y., Bengio, Y., Hinton, G. Deep learning, *Nature* **521**(7553), 436–444 (2015) <https://doi.org/10.1038/nature14539>
6. Li, P., Noah, S.A.M., Sarim, H.M. A survey on deep neural networks in collaborative filtering recommendation systems, arXiv preprint arXiv:2412.01378 (2024) <https://arxiv.org/abs/2412.01378>
7. Nápoles, G., Jastrzębska, A., Mosquera, C., Vanhoof, K., Homenda, W. Deterministic learning of hybrid fuzzy cognitive maps and network reduction approaches, *Neural Networks* **124**, 258–268 (2020) <https://doi.org/10.1016/j.neunet.2020.01.019>

8. Nápoles, G., Jastrzebska, A., Grau, I., Salgueiro, Y., León, M. A review on fuzzy cognitive mapping: Recent advances and algorithms, *Big Data and Cognitive Computing* **10**(1), 22 (2026) <https://doi.org/10.3390/bdcc10010022>
9. Papageorgiou, E.I., Hatwagner, M.F., Buruzs, A., Kóczy, L.T. A concept reduction approach for fuzzy cognitive map models, *Neurocomputing* **232**, 189–203 (2017) <https://doi.org/10.1016/j.neucom.2016.12.042>
10. Papageorgiou, E.I., Salmeron, J.L. A review of fuzzy cognitive maps research during the last decade, *IEEE Transactions on Fuzzy Systems* **21**(1), 66–79 (2013) <https://doi.org/10.1109/TFUZZ.2012.2221757>
11. Qiao, B., Liu, J., Wu, P., Teng, Y. Wind power forecasting based on variational mode decomposition and high-order fuzzy cognitive maps, *Applied Soft Computing* **129**, 109586 (2022) <https://doi.org/10.1016/j.asoc.2022.109586>
12. Rowe, E., Norton, L., McVittie, A., Watson, C., Wagner, M., Waterton, C., Smith, L. Using fuzzy cognitive mapping to assess the sustainability impacts of transitioning to pasture-fed production in the uk beef sector, *Renewable Agriculture and Food Systems* **40**, e1 (2025) <https://doi.org/10.1017/S1742170524000206>
13. Tian, C., Cheng, T., et al. A survey on deep learning fundamentals, *Artificial Intelligence Review* p. 281 (2025) <https://doi.org/10.1007/s10462-025-11368-7>
14. Wu, K., Liu, J. Learning large-scale fuzzy cognitive maps under limited resources, *Engineering Applications of Artificial Intelligence* **116**, 105376 (2022) <https://doi.org/10.1016/j.engappai.2022.105376>
15. Wu, K., Liu, J., Liu, P., Shen, F. Online fuzzy cognitive map learning, *IEEE Transactions on Fuzzy Systems* **29**(7), 1885–1898 (2021) <https://doi.org/10.1109/TFUZZ.2020.2988845>
16. Yadegari, M., Mohammadi, S. A fuzzy cognitive map approach to selecting the best knowledge management strategy, *VINE Journal of Information and Knowledge Management Systems* **55**(6), 1369–1393 (2025) <https://doi.org/10.1108/VJIKMS-07-2023-0186>
17. Zhou, Q., Ma, Y., Xing, Z., Yang, X. Sparse and regression learning of large-scale fuzzy cognitive maps based on adaptive loss function, *Applied Intelligence* **54**(3), 2750–2766 (2024) <https://doi.org/10.1007/s10489-023-05112-3>
18. Zhou, Q., Ma, Y., Xing, Z., Yang, X. Pearson correlation coefficient guided large-scale fuzzy cognitive maps learning algorithm, *Fuzzy Sets and Systems* **519**, 109523 (2025) <https://doi.org/10.1016/j.fss.2025.109523>

Keynote speech:

Harnessing AI with Limited Data: Approximate Knowledge Interpolation and Practical Applications

Qiang Shen

Department of Computer Science,
Aberystwyth University, Wales



Abstract: AI stands to transform nearly every aspect of contemporary life. Much of its success is driven by deep learning techniques that rely on vast quantities of data. Yet, a pivotal question emerges when faced with limited data for a new problem, especially if such data is ambiguously characterised. Can AI maintain its efficacy under these constraints? This talk delves into contributions addressing this query, highlighting how fuzzy rule interpolation (FRI) enables approximate reasoning in situations marked by sparse or incomplete knowledge. This is particularly relevant when traditional rule-based inference mechanisms falter because observations do not align with existing rules. The talk will centre on a prominent subset of FRI techniques, Transformation-based FRI (T-FRI). Kicking off with an exploration of the foundational T-FRI approach, it will segue into a concise overview of its expanded repertoire, each addressing certain shortcomings inherent to the original method. Subsequently, real-world applications of these methodologies will be showcased, exemplifying their potency in tackling formidable challenges in domains like network security and medical diagnosis. These cases will underscore AI's capability to function effectively even with incomplete knowledge and ambiguous data. The talk will conclude with a brief look at promising future directions in this vital area of research.

From fuzzy measures to communities: a clustering approach for interpretation

Carlos I. Pérez-Sechi, Inmaculada Gutiérrez, Javier Castro and Daniel Gómez

Complutense University of Madrid

e-mail: {cperez14, inmaguti, jcastroc, dagomez}@ucm.es

Abstract: In this paper, we address the challenge of interpreting fuzzy measures. The goal is to obtain a partition of the set of agents over which the fuzzy measure is defined, providing useful information about their relevance, interactions and contributions to coalitions. To this end, we use a network-based visualization of the agents and their relationships, obtained with the Shapley value and the interaction index. We then propose an aggregation methodology that summarizes the relevant information of a fuzzy measure into a matrix, to which we apply the Louvain algorithm in order to obtain partitions of the agents. With an appropriate representation, this network partition provides useful, clear, and immediate information about the synergies defined by the fuzzy measures over the agents.

Keywords: Fuzzy measures · Networks · Clustering · Shapley value · Interaction Index · Louvain algorithm

Acknowledgement: This research has been partially supported by the Spanish Government I+D+i Plan PID2024-155289NB-I00 funded by MICIU/AEI/10.13039/501100011033 and ERDF/EU.

References

1. Beliakov, G., James, S., Wu, J.: Discrete Fuzzy Measures: Computational Aspects, Studies in Fuzziness and Soft Computing, vol. 382. Springer, Cham (2020)
2. Blondel, V., Guillaume, J., Lambiotte, R., Lefevre, E.: Fast unfolding of communities in large networks. *Journal Of Statistical Mechanics-Theory And Experiment* (P10008) (2008)
3. Calvo, T., Mayor, G., Mesiar, R.: Aggregation operators: new trends and applications. *Physica* **97** (2012)
4. Dubois, D., Prade, H.: Criteria aggregation and ranking of alternatives in the framework of fuzzy theory. In: *Fuzzy Sets and Decision Analysis*. vol. 20, pp. 85–121. TIMS Studies in Management Science (1984)
5. Garmendia, L.: The Evolution of the Concept of Fuzzy Measure, pp. 185–200. Springer Berlin Heidelberg, Berlin, Heidelberg (2005)
6. Grabisch, M.: k-order additive discrete fuzzy measures and their representation. *Fuzzy Sets and Systems* **92**(2), 167–189 (1997)

7. Gutiérrez, I., Castro, J., Gómez, D., Espínola, R.: Calculating the interaction index of a fuzzy measure: A polynomial approach based on sampling. *Fuzzy Sets and Systems* **466**, 108454 (2023)
8. Hernández, R., Gutiérrez, I., Castro, J.: Social network analysis: A novel paradigm for improving community detection. *International Journal of Computational Intelligence Systems* **18**(1), 87 (2025)
9. Murofushi, T., Soneda, S.: Techniques for reading fuzzy measures (III): Interaction index. In: *Proceedings of the 9th Fuzzy Systems Symposium, Sapporo, Japan*. pp. 693–696 (1993)
10. Pérez-Sechi, C.I., Castro, J., Daniel Gómez, D.M., Espínola, R., Gutierrez, I.: Network visualization of a fuzzy measure. In: *Proc. 16th European Symposium on Computational Intelligence and Mathematics. A Coruña, Spain (2025)*
11. Pérez-Sechi, C.I., Gutiérrez, I., Castro, J., Gómez, D., Martín, D., Espínola, R.: On the role of relations and interactions in fuzzy systems for machine learning. *2025 IEEE International Conference on Fuzzy Systems (FUZZ)* pp. 1–6 (2025)
12. Shapley, L.S.: A value for n-person games. In: Kuhn, H.W., Tucker, A.W. (eds.) *Contributions to the Theory of Games (AM-28), Volume II*, pp. 307–318. Princeton University Press, Princeton (1953)
13. Sugeno, M.: Fuzzy measure and fuzzy integral. *Transactions of the Society of Instrument and Control Engineers* **8**(2), 218–226 (1972)

Formal Concept Analysis for Evaluating the Intent Dimension of LLMs

Adam Leiyi Chen-Abolacio and Joaquín Borrego-Díaz

Departamento de Ciencias de la Computación e Inteligencia Artificial, Universidad de Sevilla, E.T.S. Ingeniería Informática - Avda. Reina Mercedes s.n., 41006 Sevilla, Spain

e-mail: adacheabo@alum.us.es, jborrego@us.es

Abstract: We propose a framework based on Formal Concept Analysis (FCA) to audit the “intent dimension” of LLMs. By operationalizing the model as an oracle in Attribute Exploration, we introduce an entropy-based dynamic retry mechanism to mitigate stochasticity. Experiments across models (1.5B–120B) in Integer and Graph domains reveal a “Generative Gap”: models often validate abstract rules but fail to generate valid counterexamples. This structural inconsistency suggests LLMs rely on statistical correlation rather than stable conceptual grounding.

Keywords: Formal Concept Analysis · Language Models · Concept Exploration

Acknowledgement: Grant PID2023-147198NB-100, funded by MICIU /AEI/10.13039/ 501100011033 and by FEDER, UE.

References

1. Alonso-Jiménez, J.A., Aranda-Corral, G.A., Borrego-Díaz, J., Fernández-Lebrón, M.M., Hidalgo-Doblado, M.J.: Extending attribute exploration by means of boolean derivatives. In: Proc. 6th Conf. Concept Lattices and Their Applications (CLA 2008). pp. 121–132 (2008)
2. Aranda-Corral, G.A., Borrego-Díaz, J., Galán-Páez, J.: Concept learning consistency under three-way decision paradigm. *Int. J. Machine Learning and Cybernetics* **13**, 2977–2999 (2022)
3. Bengio, Y., Ducharme, R., Vincent, P., Jauvin, C.: A neural probabilistic language model. *Journal of machine learning research* **3**(Feb), 1137–1155 (2003)
4. Brown, T.B., et al.: Language models are few-shot learners. In: Proc. 34th Int. Conf. Neural Information Processing Systems (NIPS '20). Red Hook, NY, USA (2020)
5. Chen, M., Tworek, J., Jun, H., Yuan, Q., de Oliveira Pinto, H.P., Kaplan, J., Edwards, H., Burda, Y., Joseph, N., Brockman, G., Ray, A., Puri, R., Krueger, G., Petrov, M., Khlaaf, H., Sastry, G., Mishkin, P., Chan, B., Gray, S., Ryder, N., Pavlov, M., Power, A., Kaiser, L., Bavarian, M., Winter, C., Tillet, P., Such, F.P., Cummings, D., Plappert, M., Chantzis, F., Barnes, E., Herbert-Voss, A., Guss, W.H., Nichol, A., Paino, A., Tezak, N., Tang, J., Babuschkin, I., Balaji, S., Jain, S., Saunders, W., Hesse, C., Carr, A.N., Leike, J., Achiam, J., Misra, V.,

- Morikawa, E., Radford, A., Knight, M., Brundage, M., Murati, M., Mayer, K., Welinder, P., McGrew, B., Amodei, D., McCandlish, S., Sutskever, I., Zaremba, W.: Evaluating large language models trained on code (2021), <https://arxiv.org/abs/2107.03374>
6. Ganter, B., Obiedkov, S.: *Conceptual Exploration*. Springer (2016)
 7. Ganter, B., Wille, R.: *Formal Concept Analysis*. Springer, Cham, 2 edn. (2024)
 8. Holtzman, A., Buys, J., Du, L., Forbes, M., Choi, Y.: The curious case of neural text degeneration. In: *International Conference on Learning Representations*. pp. 1 – 12 (2020), <https://openreview.net/forum?id=rygGQyrFvH>
 9. Huang, J., et al.: Large language models cannot self-correct reasoning yet (2024)
 10. Petroni, F., et al.: Language models as knowledge bases? In: *Proc. 2019 Conf. on Empirical Methods in Natural Language Processing and the 9th Int. Joint Conf. on Natural Language Processing (EMNLP-IJCNLP)*. pp. 2463–2473 (2019)
 11. Winograd, T., Flores, F.: *Understanding Computers and Cognition: A New Foundation for Design*. Ablex Publishing Corporation (1986)

On the aggregation of contexts with common attributes

Roberto G. Aragón, Jesús Medina and Samuel Molina-Ruiz

Department of Mathematics. University of Cádiz, Cádiz, Spain.
e-mail: {roberto.aragon,jesus.medina,samuel.molina}@uca.es

Abstract: The aggregation of databases enables the local study of decentralized and partially overlapping information, and formal concept analysis provides a rigorous mathematical framework for addressing this task. This paper investigates the aggregation of databases with common attributes in formal concept analysis, focusing on how information is extended when passing from local data sources to a unified global system.

Keywords: Formal concept analysis · context aggregation · concept lattice

Acknowledgement: Partially supported by the project PID2022-137620NB-I00 funded by MICIU/AEI/10.13039/501100011033 and FEDER, UE, by the grant TED2021-129748B-I00 funded by MCIN/AEI/10.13039/501100011033 and European Union NextGenerationEU/PRTR, Project FEDER-UCA-2024-A2-04 funded by Programa Operativo FEDER Andalucía 2021-2027 and by Consejería de Universidad, Investigación e Innovación, Junta de Andalucía; and DGP_PRED_2024_01455 funded by the Junta de Andalucía/CUII and by FSE+.

References

1. R. G. Aragón, J. Medina, and S. Molina-Ruiz. The notion of bond in the multi-adjoint concept lattice framework. In *Advances in Artificial Intelligence*, pages 243–253, Cham, 2024. Springer Nature Switzerland.
2. R. G. Aragón, J. Medina, and S. Molina-Ruiz. Towards the aggregation of multi-adjoint concept lattices. In *Late Breaking Advances on Conceptual Structures of the 1st Int. Joint Conference on Conceptual Knowledge Structures*, 2024.
3. R. G. Aragón, J. Medina, and S. Molina-Ruiz. Context-based sum via multi-adjoint bonds. *Fuzzy Sets and Systems*, page 109771, 2026.
4. R. G. Aragón, J. Medina, and S. Molina-Ruiz. Vertical sum of concept lattices via bonds. *Studies in Computational Intelligence*, 2026. In press.
5. B. Ganter and R. Wille. *Formal Concept Analysis: Mathematical Foundations*. Springer, 2 edition, 2024.
6. J. Konecny and M. Ojeda-Aciego. On homogeneous L -bonds and heterogeneous L -bonds. *International Journal of General Systems*, 45(2):160–186, 2016.
7. O. Křídlo, Ľ. Antoni, and S. Krajčí. Selection of appropriate bonds between L -fuzzy formal contexts for recommendation tasks. *Information Sciences*, 606:21–37, 2022.

8. O. Krídlo, S. Krajčí, and M. Ojeda-Aciego. The category of L -Chu correspondences and the structure of L -bonds. *Fundamenta Informaticae*, 115:297–325, 2012.
9. O. Krídlo, D. López-Rodríguez, L. Antoni, P. Eliaš, S. Krajčí, and M. Ojeda-Aciego. Connecting concept lattices with bonds induced by external information. *Information Sciences*, 648:119498, 2023.
10. B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pages 1273–1282, 2017.
11. J. Medina, M. Ojeda-Aciego, and J. Ruiz-Calviño. Formal concept analysis via multi-adjoint concept lattices. *Fuzzy Sets and Systems*, 160(2):130–144, 2009.
12. M. Shaheen, M. S. Farooq, T. Umer, and B.-S. Kim. Applications of federated learning; taxonomy, challenges, and research trends. *Electronics*, 11(4):670, 2022.
13. W. Shi, J. Cao, Q. Zhang, Y. Li, and L. Xu. Edge computing: Vision and challenges. *IEEE internet of things journal*, 3(5):637–646, 2016.

Interactive Fuzzy FCA Recommender System: A Visual Approach using fcaR

Ángel Mora¹, Domingo López-Rodríguez¹ and Manuel Ojeda-Hernández²

¹ Departamento de Matemática Aplicada, Universidad de Málaga, Spain
e-mail: {dominlopez,amora}@uma.es

² Departamento de Álgebra, Geometría y Topología, Universidad de Málaga, Spain
e-mail: manuojeda@uma.es

Abstract: Traditional recommender systems often operate as black boxes, making them difficult to integrate into critical domains such as medical diagnosis, where explainability is mandatory. This paper introduces an interactive recommendation framework based on the navigation of Fuzzy Formal Concept Lattices. Rather than relying on offline calculations or static rule sets, our approach implements a *Guided Recommender* Algorithm that allows experts to explore the knowledge structure iteratively. By applying a *Local Zoom Strategy*, the system extracts relevant sublattices in real-time, enabling users to refine searches through attributes with fuzzy degrees of certainty.

We provide a tool called *fcaRvizFuzzy*, developed in R/Shiny, which will be integrated with the *fcaR* package in the medium term. We demonstrate the utility of the tool using the *cobre32* schizophrenia dataset, showing how a step-by-step visual refinement process facilitates rigorous decision-making support for individuals without mathematical expertise.

Keywords: Fuzzy Formal Concept Analysis · Recommender Systems · Explainable AI (XAI) · *fcaR* · Medical Diagnosis · Visualization

References

1. Adomavicius, G., Tuzhilin, A. Toward the next generation of recommender systems: a survey of the state-of-the-art and possible extensions, *IEEE Transactions on Knowledge and Data Engineering* **17**(6), 734–749 (2005) <https://doi.org/10.1109/TKDE.2005.99>
2. Akhmaturov, M., Ignatov, D.I. Context-aware recommender system based on boolean matrix factorisation. In: Yahia, S.B., Konecny, J. (eds.) *Proceedings of the Twelfth International Conference on Concept Lattices and Their Applications*, Clermont-Ferrand, France, October 13–16, 2015. *CEUR Workshop Proceedings*, vol. 1466, pp. 99–110. *CEUR-WS.org* (2015)
3. Belohlavek, R. *Fuzzy Relational Systems: Foundations and Principles*. Kluwer Academic/Plenum Publishers, New York (2002)
4. Belohlavek, R., Vychodil, V. What is a fuzzy concept lattice? In: *Proceedings of the CLA 2005 International Workshop on Concept Lattices and their Applications*. pp. 34–45. Palacký University, Olomouc, Czech Republic (2005)

5. du Boucher-Ryan, P., Bridge, D. Collaborative recommending using formal concept analysis, *Knowledge-Based Systems* **19**(5), 309–315 (2006) <https://doi.org/10.1016/j.knosys.2005.11.017>
6. Carpineto, C., Romano, G. *Concept Data Analysis: Theory and Applications*. John Wiley & Sons, Chichester, UK (2004) <https://doi.org/10.1002/0470011291>
7. Codocedo, V., Napoli, A. A semantic approach to concept lattice navigation and selection. In: *Proceedings of the 12th International Conference on Formal Concept Analysis (ICFCA)*. pp. 170–185. Springer (2015)
8. Cordero, P., Enciso, M., López-Rodríguez, D., Mora, Á. A conversational recommender system for diagnosis using fuzzy rules, *Expert Systems with Applications* **154**, 113449 (2020) <https://doi.org/10.1016/j.eswa.2020.113449>
9. Cordero, P., Enciso, M., López-Rodríguez, D., Mora, Á. fcar, formal concept analysis with r, *The R Journal* **14**(1), 341–361 (2022) <https://doi.org/10.32614/RJ-2022-014>
10. Cordero, P., Enciso, M., Mora, A., Pérez-Gámez, R. Visualizing fuzzy association rules with arulesviz, *International Journal of Computational Intelligence Systems* (2019)
11. Ganter, B., Wille, R. *Formal Concept Analysis: Mathematical Foundations*. Springer-Verlag, Berlin (1999)
12. Hahsler, M. Visualizing association rules in r. In: *Proceedings of the Workshop on Practical Data Mining* (2016)
13. Hahsler, M. arulesviz: Interactive visualization of association rules with r, *The R Journal* **9**(2), 163–175 (2017) <https://doi.org/10.32614/RJ-2017-047>
14. Hahsler, M., Chelluboina, S. Grouping association rules using pre-calculated clusters. Working Paper (2011)
15. Hanika, T., Hirth, J. Conexp-clj – a research tool for FCA. In: *Proceedings of the 15th International Conference on Formal Concept Analysis (ICFCA 2019) - Supplementary Proceedings*. vol. 2378, pp. 70–75. CEUR-WS.org (2019)
16. Lahcen, B., Kwuida, L. Lattice miner: A cooperative lattice-based data mining platform. In: *Supplementary Proceedings of ICFCA* (2010)
17. López-Rodríguez, D., Ángel Mora. fcaR: Formal Concept Analysis with R (2024), r package version 1.2.3
18. López-Rodríguez, D., Ojeda-Hernández, M., Ángel Mora, Bejines, C. Close-by-one-like algorithms in the fuzzy setting: Theory and experimentation, *Fuzzy Sets and Systems* **520**, 109574 (2025) <https://doi.org/10.1016/j.fss.2025.109574>
19. Musslin, L., Bazin, A., Huchard, M., Martin, P., Poncelet, P., Raveneau, V., Salaberry, A. FCAvizIR: Exploring relational data set’s implications using metrics and topics. In: *Proceedings of the 1st International Joint Conference on Conceptual Knowledge Structures (CONCEPTS 2024)*. Cádiz, Spain (2024)
20. Shim, J.P., Warkentin, M., Courtney, J.F., Power, D.J., Sharda, R., Carlsson, C. Past, present, and future of decision support technology, *Decision Support Systems* **33**(2), 111–126 (2002)
21. Shneiderman, B. The eyes have it: A task by data type taxonomy for information visualizations. In: *Proceedings of the IEEE Symposium on Visual Languages* (1996)
22. Yevtushenko, S.A. System of concept analysis (conexp). In: *Conceptual Structures: Logical, Linguistic, and Computational Issues* (2000)

Definition and resolution of bipolar multi-adjoint relation equations

M. Eugenia Cornejo, David Lobo and Jesús Medina

Department of Mathematics, University of Cádiz, Cádiz, Spain

e-mail: {mariaeugenia.cornejo,david.lobo,jesus.medina}@uca.es

Abstract: Recent literature has addressed bipolar fuzzy relation equations with join-irreducible right-hand side within the context of complete distributive residuated lattices. This work contributes to the advancement of the study by transitioning to the multi-adjoint paradigm, which offers a more flexible framework that weakens traditional algebraic constraints and replaces standard triangular norms with conjunctions of adjoint pairs. The present study focuses on the resolution of resolution of bipolar multi-adjoint relation equations with join-irreducible right-hand side, paying particular attention to their solution set.

Keywords: Bipolar multi-adjoint relation equation · distributive symmetric right unital multi-adjoint lattice · negation operator · join-irreducible element

Acknowledgement: Partially supported by the project the project PID2022-137620NB-I00 funded by MICIU/AEI/10.13039/501100011033 and FEDER, UE, by the grant TED2021-129748B-I00 funded by MCIN/AEI/10.13039/501100011033 and European Union NextGenerationEU/PRTR and project FEDER-UCA-2024-A2-04 funded by Programa Operativo FEDER Andalucía 2021-2027 and by Consejería de Universidad, Investigación e Innovación, Junta de Andalucía.

References

1. M. E. Cornejo, D. Lobo, and J. Medina. Bipolar multi-adjoint relation equations with join-irreducible right-hand side. *Computational and Applied Mathematics*, 45:307, 2026.
2. M. E. Cornejo, D. Lobo, and J. Medina. Solving generalized equations with bounded variables and multiple residuated operators. *Mathematics*, 8(11):1992, 2020.
3. M. E. Cornejo, D. Lobo, J. Medina, and B. De Baets. Bipolar equations on complete distributive symmetric residuated lattices: The case of a join-irreducible right-hand side. *Fuzzy Sets and Systems*, 442:92–108, 2022.
4. B. De Baets. Analytical solution methods for fuzzy relational equations. In D. Dubois and H. Prade, editors, *Fundamentals of Fuzzy Sets*, volume 7, pages 291–340. Springer US, Boston, MA, 2000.
5. J. C. Díaz and J. Medina. Multi-adjoint relation equations: Definition, properties and solutions using concept lattices. *Information Sciences*, 253:100–109, 2013.
6. S. Freson, B. De Baets, and H. De Meyer. Linear optimization with bipolar max–min constraints. *Information Sciences*, 234:3–15, 2013.
7. E. Sanchez. Resolution of composite fuzzy relation equations. *Information and Control*, 30(1):38–48, 1976.

Characterizing the solvability of bipolar sup-equations in terms of the negation operator

David Lobo and Pablo López-Molina

Department of Mathematics, University of Cádiz, Cádiz, Spain
e-mail: {david.lobo,pablo.lopezmedina}@uca.es

Abstract: Bipolar sup-equations are the building stones of bipolar fuzzy relation equations, which are a modified version of fuzzy relation equations where a negation operator is considered. The resolution of bipolar sup-equations, and therefore of bipolar fuzzy relation equations, is directly related to the relation sup-composition operator and the negation operator under consideration.

This work will focus on characterizing the solvability of bipolar sup-equations on the unit interval by imposing conditions exclusively on the negation operator. The fundamental objective is to generalize already known characterizations, which require conditions on both the sup-composition and the negation operator involved in a bipolar sup-equation.

Keywords: Bipolar sup-equation · bipolar fuzzy relation equation · negation operator · unit interval · solvability

Acknowledgement: Partially supported by the project the project PID2022-137620NB-I00 funded by MICIU/AEI/10.13039/501100011033 and FEDER, UE, by the grant TED2021-129748B-I00 funded by MCIN/AEI/10.13039/501100011033 and European Union NextGenerationEU/PRTR and project FEDER-UCA-2024-A2-04 funded by Programa Operativo FEDER Andalucía 2021-2027 and by Consejería de Universidad, Investigación e Innovación, Junta de Andalucía.

References

1. M. E. Cornejo, D. Lobo, and J. Medina. Bipolar fuzzy relation equations systems based on the product t-norm. *Mathematical Methods in the Applied Sciences*, 42(17):5779–5793, 2019.
2. M. E. Cornejo, D. Lobo, and J. Medina. Bipolar multi-adjoint relation equations with join-irreducible right-hand side. *Computational and Applied Mathematics*, 45:307, 2026.
3. M. E. Cornejo, D. Lobo, and J. Medina. On the solvability of bipolar max-product fuzzy relation equations with the product negation. *Journal of Computational and Applied Mathematics*, 354:520–532, 2019.
4. M. E. Cornejo, D. Lobo, and J. Medina. Optimization of partially monotonic functions subject to bipolar fuzzy relation equations. *Information Sciences*, 648:119497, 2023.

5. M. E. Cornejo, D. Lobo, and J. Medina. Solving generalized equations with bounded variables and multiple residuated operators. *Mathematics*, 8(11):1992, 2020.
6. M. E. Cornejo, D. Lobo, J. Medina, and B. De Baets. Bipolar equations on complete distributive symmetric residuated lattices: The case of a join-irreducible right-hand side. *Fuzzy Sets and Systems*, 442:92–108, 2022.
7. S. Freson, B. De Baets, and H. De Meyer. Linear optimization with bipolar max–min constraints. *Information Sciences*, 234:3–15, 2013.
8. P. Li and Q. Jin. On the resolution of bipolar max-min equations. *Kybernetika*, 52(4):514–530, 2016.
9. P. Li and Y. Liu. Linear optimization with bipolar fuzzy relational equation constraints using the lukasiewicz triangular norm. *Soft Computing*, 18(7):1399–1404, 2014.
10. D. Lobo, and P. López-Molina. Characterizing the solvability of bipolar equations in the unit interval. *Contemporary Mathematics*, 2026. In press.
11. E. Sanchez. Resolution of composite fuzzy relation equations. *Information and Control*, 30(1):38–48, 1976.
12. V. L. Tiwari and A. Thapar. Covering problem for solutions of max-archimedean bipolar fuzzy relation equations. *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems*, 28(04):613–634, 2020.
13. X.-P. Yang. Resolution of bipolar fuzzy relation equations with max-lukasiewicz composition. *Fuzzy Sets and Systems*, 397:41–60, 2020.

Keynote speech:

Model-based and Data-driven Low-cost Fuzzy Controllers with Servo System Applications

Radu-Emil Precup

Politehnica University of Timisoara (UPT),
Romania



Abstract: This keynote talk covers the following topics: an overview of the Process Control Group at the Politehnica University of Timișoara in Romania; data-driven versus model-free control; our contributions; the structure and tuning of two-degree-of-freedom (2-DOF) fuzzy controllers; servo system control applications; and evolving fuzzy systems in relation to control. The presentation will include transportation applications within the context of an ERA-NET Cofund Urban Accessibility and Connectivity (ENUAC) JPI Urban Europe project.

Optimizing Hierarchical Fuzzy Signatures for Masonry Compressive Strength Assessment

András Kaszás¹, Vanda O. Pomezanski² and László T. Kóczy³

¹ University of Pécs, Faculty of Engineering and Information Technologies, Boszorkány street 2, H-7624 Pécs, Hungary

e-mail: kaszas.andras@mik.pte.hu

² Structural Diagnostics and Analyses Research Group, University of Pécs, Faculty of Engineering and Information Technologies, Boszorkány street 2, H-7624 Pécs, Hungary

e-mail: pomezanski.vanda@mik.pte.hu

³ Dept. of Information Technology, Széchenyi István University Győr, Egyetem tér 1, H-9026 Győr, Hungary

e-mail: koczy@sze.hu

Abstract: Non-destructive testing methods are widely used in civil engineering. Such are estimating masonry compressive strength from in situ tests. In this paper, a hierarchical fuzzy signature model is presented, that combines visual observations with non-destructive measurements. In our previous research optimized weighted geometric mean was used for all internal aggregations, in accordance with preliminary expert proposed evaluation methods. In this research the goal was to determine more fitting aggregations by using evolutionary algorithm to determine the optimal linear combination of weighted geometric mean and weighted exponential mean operators, with all associated aggregation parameters, which were tuned so that the fuzzy-signature root output best agrees with reference compressive strengths obtained from destructive laboratory testing. To optimize the parameters of the model, two metaheuristic procedures were applied, namely, genetic algorithm and particle swarm optimization. Experiments on a real dataset showed that the optimization procedures can rather well approximate even extreme objective-function values, and validation with real measurements confirmed that the resulting model can support practical structural assessment.

Keywords: Fuzzy signature · Weighted geometric mean aggregation · Weighted exponential mean aggregation · Masonry strength · Evolutionary optimization of general aggregation.

Acknowledgement: We would like to express our gratitude to H. Bustince for the interesting question at the 2025 IFSA World Congress, when he proposed to check a much wider class of potential aggregation.

References

1. Maierhofer, C., Reinhardt, H.-W, Dobmann, G.: Non-destructive evaluation of reinforced concrete structures: Non-destructive testing methods, Woodhead (2010)
2. Ngekpe, B.: Non-destructive Testing Methods of Reinforced Concrete Structures-A Critical Review, European Academic Research, Volume 12, pp. 1005–1018 (2025)
3. Ballagi, Á., Pozna, C.R., Kóczy, L.T.: A New Fuzzy Graph and Signature Based Approach to Describe Fuzzy Situational Maps, IEEE International Conference on Fuzzy Systems (2014)
4. Bolnárka, G., Kóczy, L.T.: Decision support system for evaluating existing apartment buildings based on fuzzy signatures, *Int. J. Comput. Commun. Control*, 6(3), pp. 442–457 (2011)
5. Kaszás, A., Pomezanski, V.O., Kóczy, L.T.: Hierarchical Construction of Fuzzy Signature Models for Non-Destructive Assessment of Masonry Strength, Symmetry, 17, 1764 (2025)
6. Zadeh, L.A.: Fuzzy Sets, *Information and Control*, Volume 8, pp. 338–353 (1965)
7. Goguen, J.A.: L-fuzzy sets, *J. Math. Anal. Appl*, Volume 18, pp. 145–174 (1967)
8. Kóczy, L.T., Cornejo, M.E., Medina, J.: Algebraic structure of fuzzy signatures, *Fuzzy Sets and Systems*, Volume 418, pp. 25–50 (2021)
9. Bede, B.: *Mathematics of Fuzzy Sets and Fuzzy Logic*; Springer: London, UK (2013)
10. Zhao, R., Govind, R.: Defuzzification of fuzzy intervals. *Fuzzy Sets Syst.*, 43, 45–55 (1991)
11. Dormány, A.: Condition Assessment of Masonry of Historical Buildings, Strength Assessment Using Non-Destructive Testing Methods, Ph.D. Thesis, University of Pécs, Pécs, Hungary (2023)
12. Balázs, K., Botzheim, J., Koczy, T.L.: Comparative Analysis of Various Evolutionary and Memetic Algorithms, 10th International Symposium of Hungarian Researchers on Computational Intelligence and Informatics (2009)

Applying The Fuzzy Signatures Concepts for Linguistic Values

Nour Ammar¹ and László T. Kóczy²

¹ Budapest University of Technology and Economics, Hungary

e-mail: nour.ammar@edu.bme.hu

² John von Neumann University Kecskemét, Hungary

e-mail: koczy@tmit.bme.hu

Abstract: Fuzzy linguistic approaches are widely used in decision-making problems that rely on qualitative reasoning and human-like assessment. Their strength lies in modeling uncertainty and subjectivity through linguistic labels such as low, medium, high, etc. However, classical fuzzy linguistic models and fuzzy rule-based systems usually employ a flat representation, where linguistic variables are treated as independent attributes. This flat structure limits the ability to capture inter-variable dependencies, hierarchical relationships, and natural groupings that commonly exist in real-world problems. As a consequence, aggregation in flat models often relies on approximation, leading to information loss, reduced expressiveness, and diminished precision, especially as system complexity increases. To address these structural limitations, this paper proposes the use of Fuzzy Signatures (FSigs) as a hierarchical framework for linguistic information representation and aggregation. Fuzzy signatures enable linguistic variables to be organized into nested structures that reflect domain relationships and preserve intermediate reasoning results. By supporting flexible aggregation at multiple levels, fuzzy signatures reduce information loss, improve interpretability, and allow more accurate modeling of complex decision-making problems. The applicability of the proposed approach is illustrated through simple intelligent traffic control scenario.

Keywords: Fuzzy signatures · Linguistic variables · Linguistic Aggregation

References

1. Herrera, F., Martínez, L. A 2-tuple fuzzy linguistic representation model for computing with words, *IEEE Transactions on Fuzzy Systems* 8(6), 746–752 (2002)
2. Bouchon-Meunier, B., Moysse, G. Fuzzy linguistic summaries: Where are we, where can we go? In: *2012 IEEE Conference on Computational Intelligence for Financial Engineering & Economics (CIFEr)*, pp. 1–8. IEEE (2012)
3. Aczél, J. On weighted synthesis of judgements, *Aequationes Mathematicae* 27, 288–307 (1984)
4. Bonissone, P.P., Decker, K.S. Selecting uncertainty calculi and granularity: An experiment in trading-off precision and complexity. In: Kanal, L.H., Lemmer, J.F. (eds.) *Uncertainty in Artificial Intelligence*, pp. 217–247. North-Holland, Amsterdam (1986)

5. Bordogna, G., Pasi, G. A fuzzy linguistic approach generalizing boolean information retrieval: A model and its evaluation, *Journal of the American Society for Information Science* 27, 288–307 (1984)
6. Carlsson, C., Fuller, R. Benchmarking and linguistic importance weighted aggregations, *Fuzzy Sets and Systems* 114(1), 35–42 (2000)
7. Delgado, M., Verdegay, J.L., Vila, M.A. On aggregation operations of linguistic labels, *International Journal of Intelligent Systems* 8, 351–370 (1993)
8. Degani, R., Bortolan, G. The problem of linguistic approximation in clinical decision making, *International Journal of Approximate Reasoning* 2, 143–162 (1988)
9. Dubois, D., Prade, H. *Fuzzy Sets and Systems: Theory and Applications*. Academic Press, New York (1980)
10. Delgado, M., Herrera, F., Herrera-Viedma, E., Martínez, L. Combining numerical and linguistic information in group decision making, *Information Sciences* 107, 177–194 (1998)
11. Herrera, F., Herrera-Viedma, E., Martínez, L. A fusion approach for managing multi-granularity linguistic term sets in decision making, *Fuzzy Sets and Systems* 114(1), 43–58 (2000)
12. Herrera, F., Martínez, L. An approach for combining linguistic and numerical information based on the (2-tuple) fuzzy linguistic representation model in decision-making, *International Journal of Uncertainty, Fuzziness and Knowledge-Based Systems* 8(5), 539–562 (2000)
13. Yager, R.R. On ordered weighted averaging aggregation operators in multicriteria decision making, *IEEE Transactions on Systems, Man, and Cybernetics* 18, 183–190 (1988)
14. Yager, R.R. An approach to ordinal decision making, *International Journal of Approximate Reasoning* 12, 233–261 (1995)
15. Zadeh, L.A. The concept of a linguistic variable and its applications to approximate reasoning, Part I, *Information Sciences* 8, 199–249 (1975)
16. Zadeh, L.A. The concept of a linguistic variable and its applications to approximate reasoning, Part II, *Information Sciences* 8, 301–357 (1975)
17. Zadeh, L.A. The concept of a linguistic variable and its applications to approximate reasoning, Part III, *Information Sciences* 9, 43–80 (1975)
18. Zadeh, L.A., Kacprzyk, J. *Computing with Words in Information/Intelligent Systems*. Physica-Verlag, Heidelberg (1999)
19. Kóczy, L.T., Vámos, T., Biró, G. Fuzzy signatures. In: *Proceedings of Eurofuse-SIC*, vol. 99, pp. 210–217 (1999)
20. Pozna, C., Minculete, N., Precup, R.E., Kóczy, L.T., Ballagi, Á. Signatures: Definitions, operators and applications to fuzzy modelling, *Fuzzy Sets and Systems* 201, 86–104 (2012)
21. Zadeh, L.A. Fuzzy sets, *Information and Control* 8, 338–353 (1965)
22. Mikulás, G., Kóczy, L.T. Macro-level road network evaluation by fuzzy signature rule bases, *Hungarian Statistical Review* 4(1), 3–16 (2021)
23. Bukovics, Á., Fogarasi, G., Kóczy, L.T. Extended fuzzy signature-based model for qualification of residential buildings. In: *Computational Intelligence and Mathematics for Tackling Complex Problems*, pp. 91–97 (2020)

A First Exploration of Concept Representation in Latent Space

Arturo Fernández-Mora¹, Juan Moreno-García², David Muñoz-Valero² and Luis Martínez³

¹ Escuela de Doctorados, Universidad de Jaén, 23071, Jaén, Andalucía, Spain
e-mail: afm00108@red.ujaen.es

² Escuela de Ingeniería Industrial y Aeroespacial de Toledo, Department of Technologies and Information Systems, Universidad de Castilla-La Mancha, Avenida Carlos III, s/n, Toledo, 45071, Spain
e-mail: {david.munoz,juan.moreno}@uclm.es

³ Escuela Politécnica Superior de Jaén, Universidad de Jaén, 23071, Jaén, Andalucía, Spain
e-mail: martin@ujaen.es

Abstract: Autoencoders are models designed to learn compressed representations of data while preserving its most essential information. During the encoding process, they generate a latent space—an internal structure in which the complexity of the original data is transformed into a more compact and abstract representation. This naturally raises the question of whether the latent space captures the patterns the model has discovered in an unsupervised manner. In parallel, activation vectors provide a record of the response of individual neurons to each input, offering a complementary perspective for analysing internal representations. For these reasons, the way in which the latent space encodes conceptual information is examined by analysing activation vectors through clustering techniques, with the aim of determining whether the organisation of learned knowledge can be detected. The goal is to relate the resulting clusters to the concepts represented in the inputs. Our initial experiments focus on identifying conceptual patterns in activation vectors derived from simple and easily interpretable images, which facilitate concept detection. Once the experiments are completed, the results will be analysed and an attempt will be made to relate the emerging clusters to the underlying concepts.

In [1] an initial approach to this problem by exploring explainability in deep neural networks through the extraction of concepts learned in intermediate layers has been detailed. Autoencoders were used to analyse latent representations that model the input, filter noise, and capture relevant patterns that help identify significant features [2]. The study is divided into two complementary parts. First, an autoencoder was incorporated into an architecture designed for text polarity classification. Second, the DistilROBERTa model [3] was used to identify the dominant emotion present in each input text. Using both the extracted emotions and the neural activations, several clustering algorithms were applied to examine the conceptual organisation of the data. Cluster quality was assessed through internal cohesion and intercluster separation metrics based on

cosine similarity [4,5]. Although the results did not reveal a clear correspondence between clusters and emotions, certain groups exhibited high internal cohesion—particularly those generated with Fuzzy C-Means and Agglomerative Clustering—suggesting that clustering may still capture meaningful patterns in the latent space. These findings highlight the inherent complexity and subjectivity of emotion analysis in text, making its latent space difficult to interpret. Consequently, we propose to analyse concepts in a collection of synthetic images featuring clear and non-subjective concepts.




Fig. 1. An example of an input figure

The present experiment investigates how the position of a square within an image is represented in the latent space (Figure 1). The aim is to analyse how the model organises information within neurons and activation vectors to encode the square’s central coordinates. We seek to obtain clusters that exhibit strong internal coherence and clear separability. Given that the represented concepts are entirely objective, this experiment is expected to yield more interpretable results and improve upon the findings of our initial approach.

Keywords: interpretability · deep learning · machine learning · activation vectors · concepts

Acknowledgement: This work was supported by grants PID2020-112967GB-C32 and PID2020-112967GB-C33 funded by MCIN/AEI/10.13039/501100011033, by ERDF A Way of Making Europe and the Research Vice-Rector of the Universidad de Castilla-La Mancha.

References

1. Fernández-Mora, A., Moreno-Garcia, J., Muñoz-Valero, D., Martínez, L. Fuzzy logic for layer-wise explainability in deep neural networks: A first approach, in: Intelligent Data Engineering and Automated Learning – IDEAL 2025, Springer Nature Switzerland, Cham, pp. 35–46, 2026.
2. Scherlis, A., Sachan, K., Jermyn, A. S., Benton, J., Shlegeris, B. Polysemanticity and capacity in neural networks, arXiv preprint arXiv:2210.01892, 2022.

3. Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Stoyanov, V. RoBERTa: A Robustly Optimized BERT Pretraining Approach, arXiv preprint arXiv:1907.11692, 2019.
4. Han, J., Kamber, M., Pei, J. Data Mining: Concepts and Techniques (3rd ed.), Elsevier, 2011.
5. Jain, A. K., Murty, M. N., Flynn, P. J. Data clustering: a review. ACM Computing Surveys, Eastern Research Laboratory, Digital Equipment Corporation, Hudson, MA 31, 264–323, 1999.

Application of Intermediate Quantifiers Forming a Logical Structure of Opposition

Vilém Novák, Petra Murinova and Karel Fiala

University of Ostrava Institute for Research and Applications of Fuzzy Modeling 30. dubna 22, 701 03 Ostrava 1, Czech Republic

e-mail: {petra.murinova,vilem.novak,karel.fiala}@osu.cz

Abstract: In this paper we will present application of fuzzy natural logic to the analysis of scientific data and their description using the, so called, evaluative linguistic expressions and intermediate quantifiers. We show that their theory can be applied to data with the goal to produce summarisation of data in linguistic form.

Keywords: Fuzzy natural logic · Intermediate quantifiers · Intermediate syllogisms · Graded cube of opposition · Graded hexagon of opposition · Evaluative linguistic expressions

References

1. P. Murinová, V. Novák, A formal theory of generalized intermediate syllogisms, *Fuzzy Sets and Systems* 186 (2013) 47–80.
2. S. Boffa, P. Murinová, V. Novák, P. Ferbas, Graded cubes of opposition in fuzzy formal concept analysis, *International Journal and Approximate Reasoning* 145 (2022) 187–209.
3. P. Murinová, V. Novák, The theory of intermediate quantifiers in fuzzy natural logic revisited and the model of “many”, *Fuzzy sets and systems* 388 (2020) 56–89.
4. V. Novák, A formal theory of intermediate quantifiers, *Fuzzy Sets and Systems* 159 (10) (2008) 1229–1246.
5. P. Peterson, *Intermediate Quantifiers. Logic, linguistics, and Aristotelian semantics*, Ashgate, Aldershot, 2000.
6. V. Novák, A comprehensive theory of trichotomous evaluative linguistic expressions, *Fuzzy Sets and Systems* 159 (22) (2008) 2939–2969.
7. V. Novák, S. Lehmke, Logical structure of fuzzy IF-THEN rules, *Fuzzy Sets and Systems* 157 (2006) 2003–2029.
8. R. R. Yager, A new approach to the summarization of data, *Information Sciences* 28 (1) (1982) 69–86.
9. J. Kacprzyk, R. R. Yager, S. Zadrozny, A fuzzy logic based approach to linguistic summaries of databases, *International Journal of Applied Mathematics and Computer Science* 10 (4) (2000) 813–834.
10. P. Murinová, Graded structures of opposition in fuzzy natural logic, *Logica Universalis* 265 (2020) 495–522.
11. P. Murinová, F. Karel, V. Novák, B. Stefania, Graded hexagon of opposition in fuzzy natural logic with new intermediate quantifiers, *International Journal of Approximate Reasoning* 184 (2025) 109465.

12. K. Fiala, P. Murinová, A formal analysis of generalized Peterson's syllogisms related to graded Peterson's cube, *Mathematics* 10(6).
13. D. Dubois, H. Prade, On fuzzy syllogisms, *Comput.Intell.* 4 (1988) 171–179.
14. L. A. Zadeh, A computational approach to fuzzy quantifiers in natural languages, *Computers and Mathematics* 9 (1983) 149–184.
15. M. Pereira-Fariña, J. C. Vidal, F. Díaz-Hermida, A. Bugarín, A fuzzy syllogistic reasoning schema for generalized quantifiers, *Fuzzy Sets and Systems* 234 (2014) 79–96.
16. R. L. O. Cignoli, I. M. L. D'Ottaviano, D. Mundici, *Algebraic Foundations of Many-valued Reasoning*, Kluwer, Dordrecht, 2000.
17. V. Novák, I. Perfilieva, J. Močkoř, *Mathematical Principles of Fuzzy Logic*, Kluwer, Boston, 1999.
18. P. Andrews, *An Introduction to Mathematical Logic and Type Theory: To Truth Through Proof*, Kluwer, Dordrecht, 2002.
19. S. Peters, D. Westerståhl, *Quantifiers in Language and Logic*, Clarendon Press, Oxford, 2006.
20. V. Novák, P. Murinová, P. Ferbas, Formal analysis of Peterson's rules for checking validity of syllogisms with intermediate quantifiers, *International Journal and Approximate Reasoning* 150 (2022) 122–138.
21. R Core Team, *R: A Language and Environment for Statistical Computing*, R Foundation for Statistical Computing, Vienna, Austria (2025).
URL <https://www.R-project.org/>
22. M. Burda, Linguistic fuzzy logic in R, in: *Proc. IEEE International Conference On Fuzzy Systems (FUZZ-IEEE)*, IEEE, Istanbul, 2015, pp. 1–7.
23. K. B. Gorman, T. D. Williams, W. R. Fraser, Ecological sexual dimorphism and environmental variability within a community of antarctic penguins (genus *pygoscelis*), *PloS one* 9 (3) (2014) e90081.
24. A. M. Horst, A. P. Hill, K. B. Gorman, *palmerpenguins: Palmer Archipelago (Antarctica) penguin data*, r package version 0.1.0 (2020). doi:10.5281/zenodo.3960218.
URL <https://allisonhorst.github.io/palmerpenguins/>

Standard completeness of multi-adjoint Gödel logic

M. Eugenia Cornejo¹, Francesc Esteva², Luis Fariñas del Cerro³, Luis Godo² and Jesús Medina¹

¹ Department of Mathematics, University of Cádiz, Cádiz, Spain.

e-mail: {mariaeugenia.cornejo,jesus.medina}@uca.es

² Instituto de Investigación en Inteligencia Artificial (IIIA-CSIC), Bellaterra, Spain.

e-mail: {esteva,godo}@iiia.csic.es

³ IRIT-CNRS, Université de Toulouse, Toulouse, France.

e-mail: luis.farinas@irit.fr

Abstract: Multi-adjoint Gödel logic (MGL_{Δ}) is an algebraizable variant of the Multi-adjoint Lattice logic that was shown to be complete with respect to a corresponding class of linearly-ordered algebras. In this paper, we strengthen this completeness result in the sense that we show that MGL_{Δ} is also standard complete, that is, it is complete with respect to the proper subclass of algebras defined on the real-unit interval.

Keywords: Multi-adjoint lattice logic · Gödel Logic · Baaz Monteiro projection · Completeness

Acknowledgement: The authors are grateful to anonymous reviewers for their helpful remarks. This research has been partially supported by the projects PID2022-139835NB-C21, PID2022-137620NB-I00, funded by MICIU/AEI/10.13039/501100011033 and FEDER, UE, by the grant TED2021-129748B-I00 also funded by the European Union NextGenerationEU/PRTR and MCIN/AEI/10.13039/501100011033, and by the project FEDER-UCA-2024-A2-04 funded by Programa Operativo FEDER Andalucía 2021-2027 and by Consejería de Universidad, Investigación e Innovación, Junta de Andalucía.

References

1. A. Avron. A Tableau System for Gödel-Dummett Logic Based on a Hypersequent Calculus. In *Automated Reasoning with Tableaux and Related Methods (Tableaux'2000)*, Lecture Notes in Artificial Intelligence 1847. 98-111, 2000.
2. M. Baaz. Infinite-valued Gödel logics with 0-1-projections and relativizations. *Lecture Notes in Logic* 6, 23-33, Springer, 1996.
3. M. Baaz, A. Ciabattoni and C. G. Fermüller. Hypersequent Calculi for Gödel Logics - a Survey. *Journal of Logic and Computation*, vol. 13, no. 6, pp. 835-861, 2003.
4. W. J. Blok and D. Pigozzi. *Algebraizable Logics*. In *Memoirs of the American Mathematical Society*, vol. 396, American Mathematical Society, Providence, 1989.
5. R. Cignoli, F. Esteva, L. Godo, and A. Torrens. Basic fuzzy logic is the logic of continuous t-norms and their residua. *Soft Computing*, 4(2):106-112, 2000.

6. P. Cintula and C. Noguera. *Logic and Implication. An Introduction to the General Algebraic Study of Non-classical Logics*, Vol. 57 of *Trends in Logic*, Springer, 2021.
7. M. E. Cornejo, F. Esteva, L. Fariñas del Cerro, L. Godo, and J. Medina. A multi-adjoint lattice logic based on Gödel logic. *Studies in Computational Intelligence*, 0:1-7, 2025. In press. Abstract in ESCIM 2025.
8. M. E. Cornejo, L. Fariñas del Cerro, and J. Medina. A logical characterization of multi-adjoint algebras. *Fuzzy Sets and Systems*, 425:140–156, 2021.
9. M. E. Cornejo, L. Fariñas del Cerro, and J. Medina. Multi-adjoint lattice logic and truth-stressing hedges. *Fuzzy Sets and Systems*, 445:43–65, 2022.
10. M. E. Cornejo, L. Fariñas del Cerro, and J. Medina. Multi-adjoint lattice logic. properties and query answering. In G. Marreiros et al. editors, *Progress in Artificial Intelligence*, pages 701–712, Cham, 2022. Springer International Publishing.
11. M. E. Cornejo, J. Medina and E. Ramírez-Poussa. Multi-adjoint algebras versus non-commutative residuated structures. *Int. J. Approx. Reason.* 66: 119-138 (2015)
12. P. Hájek. *Metamathematics of Fuzzy Logic*. Kluwer Academic Press, 1998.
13. S. Jenei, F. Montagna. A Proof of Standard Completeness for Esteva and Godo’s Logic MTL. *Stud Logica* 70(2): 183-192 (2002)

From ASP to L-DINF: Towards Epistemic Dietary Agents for Personalized Nutrition

Stefania Costantini¹, Valentina Pitoni¹ and Alina Vozna^{1,2}

¹ Department of Information Engineering, Computer Science and Mathematics, University of L’Aquila, Italy

e-mail: {stefania.costantini,valentina.pitoni}@univaq.it

² University of Pisa, Largo B. Pontecorvo, Pisa, 56127, Italy

e-mail: alina.vozna@student.univaq.it

Abstract: Personalized nutrition systems balance strict constraints (e.g., allergies) and dynamic user adaptation. While Answer Set Programming (ASP) offers robust optimization, it lacks the cognitive flexibility for real-time belief revision. We introduce a hybrid dietary framework integrating ASP optimization with L-DINF, an epistemic logic for cognitive agents. This approach translates static “Blueprint Personas” into dynamic agents capable of introspection and negotiation by reasoning about beliefs, intentions, and the feasibility of actions. Implemented in the DALI agent language, this integration achieves the adaptive, explainable decision-making critical for modern dietary coaching.

Keywords: Answer Set Programming · Blueprint Personas · Epistemic Logic · Cognitive Agents · Personalized Nutrition.

References

1. Balbiani, P., Duque, D.F., Lorini, E.: A logical theory of belief dynamics for resource-bounded agents. In: Proc. of AAMAS’16. pp. 644–652. ACM (2016)
2. Baral, C.: Knowledge representation, reasoning and declarative problem solving. Cambridge university press (2003)
3. Brewka, G., Eiter, T., (eds.), M.T.: Answer set programming: Special issue. AI Magazine **37**(3) (2016)
4. Costantini, S., Tocchio, A.: A logic programming language for multi-agent systems. In: Flesca, S., Greco, S., Leone, N., Ianni, G. (eds.) Logics in Artificial Intelligence, European Conference, JELIA 2002, Proceedings. Lecture Notes in Computer Science, vol. 2424. Springer (2002)
5. Costantini, S., Formisano, A.: Answer set programming with resources. Journal of Logic and Computation **20**(2), 533–571 (2010)
6. Costantini, S., Formisano, A., Pitoni, V.: An epistemic logic for formalizing group dynamics of agents. Interaction Studies **23**(3), 391 – 426 (2022). <https://doi.org/10.1075/is.22019.cos>
7. Costantini, S., Tocchio, A.: The DALI logic programming agent-oriented language. In: Alferes, J.J., Leite, J.A. (eds.) Logics in Artificial Intelligence, 9th European Conference, JELIA 2004, Proceedings. Lecture Notes in Computer Science, vol. 3229, pp. 685–688. Springer (2004)

8. Ge, M., Ricci, F., Massimo, D.: Health-aware food recommender system. In: Proceedings of the 9th ACM Conference on Recommender Systems. pp. 333–334 (2015)
9. Gelfond, M.: Answer sets. In: Handbook of Knowledge Representation. Chapter 7. Elsevier (2007)
10. Lee, C.S., Wang, M.H., Sun, W.C., Chang, Y.C.: Intelligent healthcare agent for food recommendation at Tainan city. In: 2008 IEEE International Conference on Systems, Man and Cybernetics. pp. 1465–1470. IEEE (2008)
11. Lifschitz, V.: Answer set programming, vol. 3. Springer Cham (2019)
12. Liu, L., Guan, Y., Wang, Z., Shen, R., Zheng, G., Fu, X., Yu, X., Jiang, J.: An interactive food recommendation system using reinforcement learning. *Expert Systems with Applications* **254**, 124313 (2024)
13. Lorini, E.: Reasoning about cognitive attitudes in a qualitative setting. In: Logics in Artificial Intelligence - 16th European Conference, JELIA 2019. pp. 726–743 (2019)
14. Min, W., Jiang, S., Jain, R.: Food recommendation: Framework, existing solutions, and challenges. *IEEE Transactions on Multimedia* **22**(10), 2659–2671 (2019)
15. Monaldini, A., Vozna, A., Costantini, S., et al.: Blueprint personas in digital health transformation. In: CEUR WORKSHOP PROCEEDINGS. vol. 1388 (2024)
16. Petruzzelli, A., Musto, C., Di Carlo, M.C., Tempesta, G., Semeraro, G.: Recommending healthy and sustainable meals exploiting food retrieval and large language models. In: Proceedings of the 18th ACM Conference on Recommender Systems. pp. 1057–1061 (2024)
17. Phanich, M., Pholkul, P., Phimoltares, S.: Food recommendation system using clustering analysis for diabetic patients. In: 2010 international conference on information science and applications. pp. 1–8. IEEE (2010)
18. Prakash, K., Sivakumar, R.: Ontology-based intelligent multi-agent for diet food recommendation. *International Journal of Scientific & Engineering Research* **4**(1), 1–8 (2013)
19. Rehman, F., Khalid, O., Bilal, K., Madani, S.A., et al.: Diet-right: A smart food recommendation system. *KSII Transactions on Internet and Information Systems (TIIS)* **11**(6), 2910–2925 (2017)
20. Toledo, R.Y., Alzahrani, A.A., Martinez, L.: A food recommender system considering nutritional information and user preferences. *IEEE Access* **7**, 96695–96711 (2019)
21. Vozna, A., Monaldini, A., Costantini, S., Pitoni, V.: Scalable and explainable diet recommendations via answer set programming (2025)

Hybrid cd-implications to handle mixed information

Fernando Chacón-Gómez, M. Eugenia Cornejo and Jesús Medina

Department of Mathematics, University of Cádiz, Cádiz, Spain

e-mail: {fernando.chacon,mariaeugenia.cornejo,jesus.medina}@uca.es

Abstract: Mixed attribute implications have been introduced in Formal Concept Analysis to model positive and negative information simultaneously. This paper presents an alternative approach based on hybrid conjunctive-disjunctive attribute implications, which do not require the explicit inclusion of negative attributes to capture mixed information. In addition to considering fewer attributes, these hybrid implications also enable more comprehensive knowledge extraction due to their more flexible structure.

Keywords: Formal Concept Analysis · Mixed Information · Attribute Implications · Knowledge Extraction

Acknowledgement: Partially supported by the project PID2022-137620NB-I00 funded by MICIU/AEI/10.13039/501100011033 and FEDER, UE, by the grant TED2021-129748B-I00 funded by MCIN/AEI/10.13039/501100011033 and European Union NextGenerationEU/PRTR and by Project FEDER-UCA-2024-A2-04 funded by Programa Operativo FEDER Andalucía 2021-2027 and by Consejería de Universidad, Investigación e Innovación, Junta de Andalucía.

References

1. E. Bartl and J. Konecny. L-concept analysis with positive and negative attributes. *Information Sciences*, 360:96 – 111, 2016.
2. F. Chacón-Gómez, M. E. Cornejo, and J. Medina. Towards confirmation measures to mixed attribute implications. In M. Ojeda-Aciego, K. Sauerwald, and R. Jäschke, editors, *Graph-Based Representation and Reasoning*, pages 193–196, Cham, 2023. Springer Nature Switzerland.
3. P. Cordero, M. Enciso, A. Mora, and M. Ojeda-Aciego. Computing left-minimal direct basis of implications. In M. Ojeda-Aciego and J. Outrata, editors, *CLA*, volume 1062 of *CEUR Workshop Proceedings*, pages 293–298. CEUR-WS.org, 2013.
4. D. Dubois, J. Medina, H. Prade, and E. Ramírez-Poussa. Disjunctive attribute dependencies in formal concept analysis under the epistemic view of formal contexts. *Information Sciences*, 561:31–51, 2021.
5. B. Ganter, G. Stumme, and R. Wille, editors. *Formal Concept Analysis: Foundations and Applications*. Lecture Notes in Computer Science. Springer Verlag, 2005.

6. B. Ganter and R. Wille. *Formal Concept Analysis: Mathematical Foundation*. Springer Verlag, 1999.
7. J.-L. Guigues and V. Duquenne. Familles minimales d'implications informatives résultant d'un tableau de données binaires. *Mathématiques et Sciences Humaines*, 95:5–18, 1986.
8. J. Rodríguez-Jiménez, P. Cordero, M. Enciso, and A. Mora. Negative attributes and implications in formal concept analysis. *Procedia Computer Science*, 31:758 – 765, 2014.
9. J. Rodríguez-Jiménez, P. Cordero, M. Enciso, and S. Rudolph. Concept lattices with negative information: A characterization theorem. *Information Sciences*, 369:51 – 62, 2016.
10. R. Wille. Restructuring lattice theory: an approach based on hierarchies of concepts. In I. Rival, editor, *Ordered Sets*, pages 445–470. Reidel, 1982.

Towards the non recursive notion of pseudo-intent in residuated concept lattices with hedges

M. Eugenia Cornejo, Jesús Medina and Francisco J. Ocaña-Alcázar

Department of Mathematics, University of Cádiz, Cádiz, Spain

e-mail: {mariaeugenia.cornejo,jesus.medina,franciscojose.ocana}@uca.es

Abstract: Pseudo-intents play an important role in the computation of attribute implication bases in residuated concept lattices with hedges. In this paper, we propose a non-recursive notion of pseudo-intent for the residuated framework with the aim of providing deeper conceptual insight and clarifying its structural properties. We study the relationship between this new notion and the previously established recursive definition, identifying conditions under which the two notions are equivalent.

Keywords: Pseudo-intent · residuated concept lattice · truth-stressing hedge · attribute implication.

Acknowledgement: Partially supported by the project PID2022-137620NB-I00 funded by MICIU/AEI/10.13039/501100011033 and FEDER, UE, by the grant TED2021-129748B-I00 funded by MCIN/AEI/10.13039/501100011033 and European Union NextGenerationEU/PRTR and by Project FEDER-UCA-2024-A2-04 funded by Programa Operativo FEDER Andalucía 2021-2027 and by Consejería de Universidad, Investigación e Innovación, Junta de Andalucía.

References

1. R. Bělohlávek and V. Vychodil. Formal concept analysis and linguistic hedges. *Int. J. General Systems*, 41(5):503–532, 2012.
2. R. Bělohlávek and V. Vychodil. Attribute dependencies for data with grades I. *International Journal of General Systems*, 45(7-8):864–888, 2016.
3. B. Davey and H. Priestley. *Introduction to Lattices and Order*. Cambridge University Press, second edition, 2002.
4. D. Dubois, J. Medina, and H. Prade. Extracting attribute implications from a formal context: Unifying the basic approaches. *Information Sciences*, 689:121419, 2025.
5. B. Ganter. Two basic algorithms in concept analysis. In L. Kwuida and B. Sertkaya, editors, *Formal Concept Analysis*, pages 312–340, Berlin, Heidelberg, 2010. Springer Berlin Heidelberg.
6. B. Ganter and R. Wille. *Formal Concept Analysis: Mathematical Foundation*. Springer Verlag, 1999.

7. J.-L. Guigues and V. Duquenne. Familles minimales d'implications informatives résultant d'un tableau de données binaires. *Mathématiques et Sciences Humaines*, 95:5–18, 1986.
8. P. Hájek. On very true. *Fuzzy Sets and Systems*, 124(3):329 – 333, 2001.
9. M. Ojeda-Hernández, I. P. Cabrera, P. Cordero, and E. Muñoz-Velasco. On pseudointents in fuzzy formal concept analysis. In M. Ojeda-Aciego, K. Sauerwald, and R. Jäschke, editors, *Graph-Based Representation and Reasoning*, pages 36–40, 2023.
10. R. Radim Bělohávek. Fuzzy galois connections. *Mathematical Logic Quarterly*, 45(4):497–504, 1999.

A hybrid framework for integrating three-valued and fuzzy Formal Concept Analysis

Manuel Enciso, Pablo Cordero, Ángel Mora and Francisco Pérez-Gámez

Universidad de Málaga, Spain

e-mail: {enciso,pcordero,amora,franciscoperezgamez}@uma.es

Abstract: Formal Concept Analysis (FCA) is a fundamental tool for extracting knowledge from data organized in a formal context. Its theoretical foundation stems from the notion of Galois connections and generalizations of Birkhoff’s theorem. The extracted knowledge can be expressed in two ways: as a set of attribute implications (a theory) or as a formal concept lattice (a hierarchy of concepts). Since its inception [1], several extensions of FCA theory have been developed to model different types of information within a formal context. Such extensions require generalizing the notion of formal context and the underlying Galois connection on which the machinery relies. Furthermore, this process necessitates a broader generalization of both attribute implications and formal concepts. Our research focuses primarily on how missing information is treated and interpreted, highlighting the strong relationship between this issue and the semantics of negation.

One of the early extensions in this area [2] proposed that if an object cannot be affirmed to possess an attribute, the negation of that affirmation is assumed. While this initial approach lacked the expressive power to capture the complexity of real-world data, it provided a necessary foundation for further study. Consequently, in [3], we explored this framework and developed a sound and complete axiomatic system where missing information is treated as negation.

A second step, more suitable for real-world applications, involves distinguishing between negated and unknown information. In [4], we introduced a three-valued framework to capture all possibilities: affirmed, negated, or unknown. Although various approaches incorporate three-valued logic—often integrated into different frameworks and analyzed in detail in [5]—our approach [4] adopts an ordering of truth values induced by the amount of knowledge, similar to the bilattice approach [6]. Additionally, we defined several sound and complete axiomatic systems with distinct orientations.

Furthermore, a prominent line of FCA extensions is framed within fuzzy set theory, with numerous works developing fuzzy generalizations [7,8,9]. The integration of these fuzzy frameworks with the aforementioned three-valued perspective leads to the consideration of interval-valued or intuitionistic logic. While initial works exist in this area [10,11], both semantics differ and they are not equivalent. In this work, we propose an extension of FCA rooted in our previ-

ous research [4], blending it with other approaches within the intuitionistic or interval-valued paradigms.

Keywords: Formal Concept Analysis, unknown information, Intuitionistic

References

1. Ganter, B. and Wille, R. Applied Lattice Theory: Formal Concept Analysis In General Lattice Theory, G. Grätzer editor, Birkhäuser, 1997.
2. Missaoui, R., Nourine, L. and Renaud, Y. Computing Implications with Negation from a Formal Context, *Fundamenta Informaticae*, IOS Press, volume 115, number 4, pages 357–375, 2012.
3. Cordero, P., Enciso, M., Mora, A. and Rodriguez-Jiménez, J. M. Inference of Mixed Information in Formal Concept Analysis. In: *Trends in Mathematics and Computational Intelligence*, Springer International Publishing, pages 81–87, 2019.
4. Pérez-Gámez, F., Cordero, P., Enciso, M. and Mora, A. Simplification logic for the management of unknown information, *Information Sciences*, volume 634, pages 505-519, 2023.
5. Ciucci, D., Dubois, D. and Lawry, J. Borderline vs. unknown: comparing three-valued representations of imperfect information, *Intl J of Approximate Reasoning*, volume 55, number 9, pages 1866-188, 2014.
6. Fitting, M. Bilattices and the semantics of logic programming, *The Journal of Logic Programming*, volume 11, number 2, pages 91-116, 1991.
7. Bělohlávek, R. Fuzzy Galois Connections, *Mathematical Logic Quarterly*, 45: 497-504, 1999.
8. Medina, J., Ojeda-Aciego, M., Ruiz-Calviño, J. Formal concept analysis via multi-adjoint concept lattices, *Fuzzy Sets and Systems*, volume 160, number 2, pages 130–144, 2009.
9. Dubois, D., Medina, J., Prade, H. and Ramírez-Poussa, H. Disjunctive attribute dependencies in formal concept analysis under the epistemic view of formal contexts, *Information Sciences*, volume 561, pages 31–51, 2021.
10. Konecny, J. Attribute implications in L-concept analysis with positive and negative attributes: Validity and properties of models, *International Journal of Approximate Reasoning*, Elsevier, volume 120, pages 203–215, 2020.
11. Kridlo, O. and Ojeda-Aciego, M. Extending formal concept analysis using intuitionistic l-fuzzy sets, 2017 IEEE International Conference on Fuzzy Systems (FUZZ-IEEE), Naples, Italy, pages 1–6, 2017.

Keynote speech:

Fuzzy Models in Anytime Systems

Annamária R. Várkonyi-Kóczy^{1,2}

¹ Department of Information Technologies,
John von Neumann University, Kecskemét, Hungary

² Department of Informatics, J. Selye University,
Slovakia



Abstract: In resource, data, and time insufficient conditions, anytime algorithms, models, and systems can be used advantageously. Anytime systems are real-time systems with the aim to provide continuous operation in case of changing circumstances and to avoid critical breakdowns in cases of missing input data, temporary shortage of time, or computational power. Naturally, while the information processing can be maintained, the complexity must be reduced, thus the results of the computing become less accurate. Although, it is ensured that the results are the best in the given circumstances and that the error of the output is always known. Embedding fuzzy (and neural network) models in anytime systems extends the advantages of anytime systems, e.g. with respect to the transient behavior of the dynamic systems. Unfortunately, however, in many cases we face difficulties finding appropriate fuzzy models to be adopted. The talk focuses on different methods and techniques that can be applied to transform ‘classical’ fuzzy models into appropriate models for easy and effective anytime use. The concepts and techniques of anytime systems together with solutions of anytime fuzzy (and neural) approaches will be addressed. To illustrate efficiency, in the presentation, several applications will also be discussed, focusing on areas such as signal-, image processing, fault diagnosis, and control.

Difference between divisibility and smoothness for pseudo-t-norms on finite lattices

Juraj Kalafut¹, Martin Kalina¹, Ivona Hrivová² and Andrea Mesiarová-Zeménková^{3,4}

¹ Department of Mathematics and Descriptive Geometry, Faculty of Civil Engineering, Slovak University of Technology in Bratislava, Radlinského 11, 810 05 Bratislava, Slovakia

e-mail: {juraj.kalafut, martin.kalina}@stuba.sk

² Institute of Computer Science and Mathematics, Faculty of Electrical Engineering and Information Technology, Slovak University of Technology in Bratislava, Ilkovičova 3, 841 04 Bratislava, Slovak Republic

e-mail: ivona.hrivova@stuba.sk

³ Mathematical Institute, Slovak Academy of Sciences, Štefánikova 49, 814 73 Bratislava, Slovakia

e-mail: zemankova@mat.savba.sk

⁴ Institute for Research and Applications of Fuzzy Modeling, University of Ostrava, CE IT4Innovations, 30. dubna 22, 701 03 Ostrava, Czech Republic

Abstract: Continuous t-norms are undoubtedly the most studied t-norms. However, continuity is not a suitable notion for finite lattices. Therefore, smoothness, divisibility, 1-Lipschitzianity, and the intermediate value property were proposed as suitable counterparts of continuity.

This paper is devoted to studying these properties of t-norms on finite lattices. These three properties coincide only on some special types of lattices. Smoothness and divisibility are shown to be independent properties of t-norms, in general. Furthermore, on finite lattices with incomparable elements, divisibility and smoothness of pseudo-t-norms do not necessarily imply commutativity, which differs from the situation of pseudo-t-norms on finite chains.

Keywords: T-norm · finite lattice · divisibility · smoothness · pseudo-t-norm · intermediate value property

Acknowledgement: The authors acknowledge the support of the grants VEGA 1/0036/23 and VEGA 2/0128/24.

References

1. G. Grätzer (2011). *Lattice Theory*. Springer Basel AG. ISBN 978-3-0348-0017-4.
2. E. P. Klement, R. Mesiar, E. Pap (2000). *Triangular norms*. Kluwer Academic Publishers, Dordrecht.

3. F. Kouchakinejad, A. Stupňanová, A. Šeliga (2023). A note on divisible discrete triangular norms. *Iranian Journal of Fuzzy Systems* 19(1), pp. 73–81.
4. G. Mayor, J. Torrens, (2005). Triangular-norms on discrete settings. In: *Logical, Algebraic, Analytic, and Probabilistic Aspects of Triangular Norms* (Eds E.P.Klement, R. Mesiar), pp. 189–230.
5. Y. Su, Y. Su, R. Mesiar (2023). Divisible associative aggregation operations on finite chains. *Iranian Journal of Fuzzy Systems* 20(5), pp. 1–8.

Codomain lattice and optimization problems

Vanja Stepanović¹ and Andreja Tepavčević^{2,3}

¹ University of Belgrade, Faculty of Agriculture, 11080 Belgrade, Nemanjina 6, Serbia
e-mail: vanja@agrif.bg.ac.rs

² Mathematical Institute of the Serbian Academy of Sciences and Arts, Kneza Mihaila 36, 11000 Beograd, Serbia

³ University of Novi Sad, Faculty of Sciences, Trg Dositeja Obradovića 3, Novi Sad, Serbia
e-mail: andreja@dmi.uns.ac.rs

Abstract: The paper gives a survey of the existing knowledge about optimal solutions to lattice-valued relational equations and inequations, adding some new results to complete what is still lacking. A necessary and sufficient condition for having the greatest solution of the typical inequation is the infinite distributivity of the codomain lattice. The least solution, however, need not exist even in the crisp case. Meet-continuity of the codomain lattice is a sufficient condition for the existence of a maximal solution to any system of relational equations and inequations. A maximal solution may not exist without meet-continuity, even if the codomain lattice is distributive. However, we give an example proving that - in case of a finite domain set - meet-continuity is not necessary condition for having a maximal solution to all typical inequations. A minimal solution does not exist in the case of a residual codomain lattice. It may not exist even in a more special case of complete Heyting codomain lattice.

Keywords: Lattice-valued relational (in)equation · The greatest solution · The least solution · A maximal solution · A minimal solution

Acknowledgement: This research was supported by the Science Fund of the Republic of Serbia, Grant no 6565, Advanced Techniques of Mathematical Aggregation and Approximative Equations Solving in Digital Operational Research - AT-MATADOR. The authors also gratefully acknowledge the financial support of the Ministry of Science, Technological Development and Innovation of the Republic of Serbia (Grants No. 451-03-34/2026-03/200116, 451-03-33/2026-03/200125, 451-03-34/2026-03/ 200125).

References

1. W. Pedrycz, "Fuzzy relational equations: bridging theory, methodology and practice," *International Journal of General Systems*, **29(4)**, 529–554, 2007.
2. J. A. Goguen, "L-Fuzzy Sets", *Journal of Mathematical Analysis and Applications*, vol. 18, pp. 145–174, 1967.

3. Sanchez, E.: Resolution of composite fuzzy relation equations. *Information and Control* **30** (1), 38–48 (1976).
4. Stepanović, V.: Two sufficient conditions for having a maximal solution. In: *Computational Intelligence and Mathematics for Tackling Complex Problems* 6, 19–26 (2025)
5. Stepanović, V.: Fuzzy set inequations and equations with a meet-continuous codomain lattice. *Journal of Intelligent and Fuzzy Systems* **34** (6), 4009–4021 (2018)
6. Stepanović, V., Tepavčević, A. A Note on the Solutions to Lattice-valued Relational Equations and Inequations, *Acta Polytechnica Hungarica* **22**(12), 27–46 (2025)
7. Stepanović, V., Tepavčević, Complete meet-continuous codomain lattice and extremal solutions of L-valued fuzzy relation equations, submitted to *Computer Science and Information Systems*.
8. Díaz-Moreno J.C., Medina J., Turunen E.: Minimal solutions of general fuzzy relation equations on linear carriers. An algebraic characterization. *Fuzzy Sets and Systems* **311**, 112–123 (2017)
9. Stepanović, V.; Tepavčević, A. Fuzzy sets (in)equations with a complete codomain lattice. *Kybernetika* **2022**, 58, 145–162, <https://doi.org/10.14736/kyb-2022-2-0145>.

Omega-algebras in classical fuzzy setting

Vanja Stepanović¹, Andreja Tepavčević^{2,3} and Aleksandar Trkulja³

¹ University of Belgrade, Faculty of Agriculture, 11080 Belgrade, Nemanjina 6, 11080 Beograd-Zemun, Serbia

e-mail: vanja@agrif.bg.ac.rs

² Mathematical Institute of the Serbian Academy of Sciences and Art, Kneza Mihaila 36, 11000 Beograd, Serbia

e-mail: andreja@dmi.uns.ac.rs

³ University of Novi Sad, Faculty of Sciences, Trg Dositeja Obradovića 3, 21102 Novi Sad, Serbia

Abstract: An Ω -algebra is an algebra paired with a lattice-valued equality, i.e., with a symmetric and transitive fuzzy relation, compatible with all the algebra operations. Its cuts are weak congruence relations of the initial crisp algebra and vice versa; if in an Ω -algebra all the cuts are weak congruences, it is a fuzzy equality. In this paper, we take the classical fuzzy relations and get some specific properties: the cuts of the fuzzy weak-congruence relations of an Ω -algebra form complete chains in the weak congruence lattice of the initial crisp algebra. Starting from this, we prove that any complete finite or countable chain-sublattice of the weak congruence lattice of an algebra can be represented as a chain of cuts of an Ω -algebra with the same crisp algebra. We illustrate the property we prove with two examples of chains in the weak congruence lattices of algebras, represented with the family of cuts of Ω -groups.

Keywords: Ω -algebra · fuzzy equality · weak congruences

Acknowledgement: This research was supported by the Science Fund of the Republic of Serbia, # Grant no 6565, Advanced Techniques of Mathematical Aggregation and Approximative Equations Solving in Digital Operational Research-AT-MATADOR.

References

1. Jimenez, J., Serrano, M.L., Šešelja, B., Tepavčević, A: Omega-rings, Fuzzy Sets and Systems **455**, 183–197 (2023).
2. Krapež, A., Šešelja, B., Tepavčević, A: Solving linear equations by fuzzy quasi-groups techniques, Information Sciences **491**, 179–189 (2019).
3. Šešelja, B., Tepavčević, A.: Ω -group in the Language of Ω -groupoids, Fuzzy Sets and Systems **397**, 152–167 (2019).
4. Budimirović, B., Budimirović, V., Šešelja, B., Tepavčević, A.: Fuzzy Identities with Application to Fuzzy Semigroups, Information Sciences, 266, (2014), 148–159.

5. Budimirović, B., Budimirović, V., Šešelja, B., Tepavčević, A.: *E-Fuzzy Groups*, *Fuzzy Sets and Systems* 289, (2016), 94–112.
6. Edeghagba, E.E., Šešelja, B., Tepavčević, A.: *Omega-Lattices*, *Fuzzy Sets and Systems* 311, (2017), 53–69.
7. Fourman, M.P., Scott, D.S.: *Sheaves and Logic*, in: M.P. Fourman, C.J. Mulvey D.S. Scott (Eds.), *Applications of Sheaves*, *Lecture Notes in Mathematics*, vol. 753, Springer, Berlin, Heidelberg, New York, 302–401 (1979).
8. Höhle, U.: *Fuzzy Sets and Sheaves. Part I: Basic Concepts*, *Fuzzy Sets and Systems*, 158 (11), 1143–1174 (2007).
9. Šešelja, B., Tepavčević, A.: *Weak congruences in universal algebra*, *Symbol Novi Sad*, 2002.
10. Šešelja, B., Tepavčević, A.: *Ω -algebras*, *Proceedings of Hawaii 2018, A conference in honor of Ralph Freese, William Lampe, and J.B. Nation*, (2018) 96–106.

Fairness Distortion Index: A Fuzzy Aggregation Framework for Evaluating League Scheduling Bias

Boldizsár Tüü-Szabó¹ and László T. Kóczy^{1,2}

¹ Széchenyi István University, Department of Information Technology, Győr, Hungary.

e-mail: {tuu.szabo.boldizsar, koczy}@sze.hu

² Telecommunications and Media Informatics, Budapest University of Technology and Economics, Budapest, Hungary.

Abstract: The structure of a league schedule can influence competitive outcomes independently of team strength, raising concerns about procedural fairness. Previous research introduced a Monte Carlo-based framework for measuring schedule-induced distortions using two indicators: the Total Fairness Bias (TFB), quantifying the overall deviation of final standings from an unbiased reference, and the Gini index, expressing how unevenly this distortion is distributed among teams. Although this two-dimensional description offers valuable insight, it does not provide a single value that supports straightforward comparisons between leagues, seasons, or alternative scheduling procedures. Moreover, identical numerical values of TFB or Gini may represent different fairness levels across competitions with distinct structural properties. To address these limitations, this paper proposes the Fairness Distortion Index (FDI), a Mamdani-type fuzzy inference system that aggregates TFB and Gini into a unified scalar measure in the interval $[0,1]$. The FDI distinguishes between ethically different distortion patterns – most notably, small global distortions that disadvantage only a few teams versus systemic distortions that affect all participants equally. As such, the FDI yields an interpretable and context-sensitive measure of unfairness. Beyond retrospective evaluation, it can serve as an optimisation objective in schedule generation, enabling the search for fixture lists that minimise competitive bias under existing competition formats.

Keywords: Fuzzy systems · Fairness measurement · Sports competitions

Acknowledgement: This work was supported by the EKÖP-25-4-II-SZE-144 University Re-search Fellowship Program of the Ministry for Culture and Innovation from the source of the National Research, Development and Innovation Fund.

References

1. Kendall, G., Knust, S., Ribeiro, C.C., Urrutia, S.: Scheduling in sports: An annotated bibliography. *Comput. Oper. Res.* 37(1), 1–19 (2010)

2. Scarf, P.A., Yusof, M.M.: A numerical study of tournament structure and seeding policy for the soccer World Cup Finals. *Statistica Neerlandica* 65(1), 43–57 (2011)
3. Goossens, D., Spieksma, F.: Scheduling the Belgian soccer league. *Interfaces* 39(2), 109–118 (2009)
4. Guyon, J.: Rethinking the FIFA World Cup final draw. *J. Quant. Anal. Sports* 11(3), 169–182 (2015)
5. Túú-Szabó, B., Kóczy, L.T.: A Monte Carlo Framework for Procedural Fixture Fairness Evaluation in League Competitions. *Annals of Operations Research* (under review, 2025)
6. Zadeh, L.A.: The concept of a linguistic variable and its application to approximate reasoning. *Inf. Sci.* 8, 199–249 (1975)
7. Mamdani, E.H., Assilian, S.: An experiment in linguistic synthesis with a fuzzy logic controller. *Int. J. Man-Mach. Stud.* 7(1), 1–13 (1975)
8. Fort, R., Quirk, J.: Cross-subsidization, incentives, and outcomes in professional team sports leagues. *J. Econ. Lit.* 33(3), 1265–1299 (1995)
9. Zimbalist, A.S.: Competitive balance in sports leagues: An introduction. *J. Sports Econ.* 3(2), 111–121 (2002)

From Voting to Aggregation: An Aggregation-Based Interpretation of Alternative Voting Mechanisms in the Fuzzy Hough Transform

Szilvia Nagy and Brigita Sziová

Department of Telecommunications, Széchenyi István University, Győr, Hungary
e-mail: nagysz@sze.hu

Abstract: The Hough transform and its fuzzy extensions are traditionally formulated as voting-based procedures in a discretized parameter space. While numerous alternative voting mechanisms have been proposed to improve robustness and reduce the influence of noise, their relation to aggregation theory has received limited explicit attention. In this paper, we reinterpret voting in the linear fuzzy Hough transform as an aggregation process that fuses local fuzzy evidence into global line hypotheses. We show that classical, fuzzy, and alternative weighted voting schemes can be viewed as specific instances of aggregation operators applied to per-point fuzzy contributions in the accumulator space. This aggregation-based viewpoint provides a unifying framework for analyzing robustness, peak concentration, and suppression of spurious maxima. The proposed interpretation is illustrated using a synthetic benchmark and the analysis of grid structures in electrocardiogram (ECG) images, where dense and repetitive line patterns can yield many local maxima under naive voting. Placeholder experiments indicate that aggregation-driven voting can improve dominant orientation estimation and reduce spurious peaks in highly structured scenes. The framework is general and can be extended to other parametric curves and application domains.

Keywords: Fuzzy Hough transform · aggregation functions · voting mechanisms · line detection · ECG image analysis

References

1. Hough, P.V.C. Machine Analysis of Bubble Chamber Pictures. In: Proc. 2nd Int. Conf. on High-Energy Accelerators and Instrumentation (1959)
2. Ballard, D.H. Generalizing the Hough Transform to Detect Arbitrary Shapes, *Pattern Recognition* **13**(2), 111–122 (1981)
3. Xu, L., Oja, E. Randomized Hough Transform (RHT): Basic Mechanisms, Algorithms, and Computational Complexities, *CVGIP: Image Understanding* **57**(2), 131–154 (1993)
4. Cucchiara, R., Filicori, F. The Vector–Gradient Hough Transform, *IEEE Trans. Pattern Analysis and Machine Intelligence* **20**(7), 746–750 (1998)

5. Han, J.H., Kóczy, L.T., Poston, T. Fuzzy Hough Transform, *Pattern Recognition Letters* **15**(7), 649–658 (1994)
6. Montseny, E., Sobrevilla, P., Mares Martí, P. Edge Orientation-Based Fuzzy Hough Transform (EOFHT). In: Proc. EUSFLAT (2003)
7. Nagy, S., Kovács, M., Sziová, B., Kóczy, L.T. Fuzzy Hough Transformation in Aiding Computer Tomography-Based Liver Diagnosis. In: *IEEE AFRICON* (2019)
8. Nagy, S., Solecki, L., Sziová, B., Sarkadi-Nagy, B., Kóczy, L.T. Applying Fuzzy Hough Transform for Identifying Honed Microgeometrical Surfaces. In: Kóczy, L. et al. (eds.) *Computational Intelligence and Mathematics for Tackling Complex Problems*. Studies in Computational Intelligence, vol. 819, pp. 35–42. Springer (2020)
9. Nagy, S., Ismail, R., Sziová, B., Kóczy, L.T. On Classical and Fuzzy Hough Transform in Colonoscopy Image Processing. In: *IEEE AFRICON* (2021)
10. Ismail, R., Prukner, P., Nagy, S. On Applying Gradient Based Thresholding on the Canny Edge Detection Results to Improve the Effectiveness of Fuzzy Hough Transform for Colonoscopy Polyp Detection Purposes. In: *New Approaches for Multidimensional Signal Processing (NAMSP 2022)*. Smart Innovation, Systems and Technologies, vol. 332, pp. 110–121. Springer (2023)
11. Ismail, R., Nagy, S. A Novel Gradient Weighted Voting Approach for Classical and Fuzzy Circular Hough Transforms and Their Application in Colonoscopy Image Analysis, *Applied Sciences* (MDPI), pre-publication/peer-review draft (2023)

On aggregation of T_M -fuzzy vector subspaces

Dragan Jočić¹ and Ivana Štajner-Papuga²

¹ Mathematical Institute of the Serbian Academy of Sciences and Arts, Serbia
e-mail: jovicndragan@gmail.com

² Department of Mathematics and Informatics, Faculty of Sciences, University of Novi Sad, Serbia

e-mail: ivana.stajner-papuga@dmi.uns.ac.rs

Abstract: Aggregation operators, as mathematical tools, play an important role in fusing data within many areas and disciplines. When the data to be aggregated have a specific structure, it is particular interest to know under which condition this structure is preserved under aggregation. In this paper focus is on n -ary aggregation of special classes of fuzzy vector subspaces on sets. The obtained results extend previously obtained ones for binary aggregation of T_M -fuzzy vector subspaces on sets.

Keywords: aggregation operators · t-norms · fuzzy sets · T_M -fuzzy vector subspaces

Acknowledgement: This research was supported by the Science Fund of the Republic of Serbia, Grant no 6565, Advanced Techniques of Mathematical Aggregation and Approximative Equations Solving in Digital Operational Research-AT-MATADOR.

References

1. Ardanza-Trevijano, S., Chasco, M.J., Elorza, J., de Natividade, M., Talavera, F.J.: Aggregation of T-subgroups. *Fuzzy Sets and Systems* *463*, 108390 (2023).
2. Bejines, C., Chasco, M.J., Elorza, J.: Aggregation of fuzzy subgroups. *Fuzzy Sets and Systems* *418*, 170–184 (2021).
3. Bejines, C., Ardanza-Trevijano, S., Chasco, M.J., Elorza, J.: Aggregation of indistinguishability operators. *Fuzzy Sets and Systems* *446*, 53–67 (2022).
4. Bejines, C.: Aggregation of fuzzy vector spaces. *Kybernetika* *59(5)*, 752–767 (2023).
5. Das, P.: Fuzzy vector spaces under triangular norms. *Fuzzy Sets and Systems* *25*, 73–85 (1988).
6. Grabisch, M., Marichal, J., Mesiar, R., Pap, E.: *Aggregation Functions*. Cambridge University Press (2009)
7. Jočić, D., Štajner-Papuga, I.: A note on aggregation of t-norm based fuzzy vector subspaces. *Acta Polytechnica Hungarica* **22** (12), 115–126 (2025)
8. Katsaras, A., Liu, D.: Fuzzy vector spaces and fuzzy vector topological spaces. *Journal of Mathematical Analysis and Applications* *58*, 135–146 (1977).
9. Klement, E. P., Mesiar, R., Pap, E.: *Triangular Norms*. Kluwer Academic Publishers, Dordrecht (2000)

10. Pedraza, T., Rodriguez-Lopez, J., Valero, O.: Aggregation of fuzzy quasi-metrics. *Information Sciences* 581, 362–389 (2021).
11. Štajner-Papuga, I., Tepavčević, A.: A note on aggregation of T subgroups. In: *Computational Intelligence and Mathematics for Tackling Complex Problems 6*, *Studies in Computational Intelligence*, Springer, accepted (2025)
12. Talavera, F.J., Ardanza-Trevijano, S., Bragard, J., Elorza, J.: Aggregation of T-subgroups of groups whose subgroup lattice is a chain. *Fuzzy Sets and Systems* 473, 108717 (2023).
13. Talavera, F.J., Ardanza-Trevijano, S., Bragard, J., Elorza, J.: New type of domination to characterize the preservation of T-subgroups under aggregation. *Fuzzy Sets and Systems* 498, 109139 (2025).
14. Zadeh, L.A.: Fuzzy sets. *Information and Control* 8, 338–353 (1965).

On discrete Sugeno integral and aggregation of algebraic objects

Ivana Štajner-Papuga¹ and Andreja Tepavčević^{1,2}

¹ Department of Mathematics and Informatics, Faculty of Sciences, University of Novi Sad, Serbia

e-mail: ivana.stajner-papuga@dmi.uns.ac.rs

² Mathematical Institute of the Serbian Academy of Sciences and Arts, Serbia

e-mail: andreja@dmi.uns.ac.rs

Abstract: It is well known that, algebraically speaking, the family of all substructures of a structure is closed under intersection. However, the union, that can be viewed as a form of aggregation, preserve the given structure only in certain cases, e.g., the union of two subgroups is a subgroup if and only if one of them is contained in the other one. Similar to the classical setting, aggregation of two fuzzy subgroups does not have to result in a fuzzy subgroup. A few specific situations with a positive result are described in [1,2,9], however, the aggregation processes of specific type of lattice-valued algebraic structures remains a field of interest for the further investigation, specially directed towards studies on the types of aggregation operators that are convenient for different uses of empirical data. Since the approach is lattice-valued, the assumption is that the aggregation operators are compatible with the lattice structure ([4]). Therefore, the focus of this research is on discrete Sugeno integral as an aggregation operator, as well as on Ω -groups, where Ω is a complete distributive lattice ([7]), and fuzzy groups as input structures.

Some recent results concerning aggregation of Ω -groups can be found in [8]. Since a function $f: [0, 1]^n \rightarrow [0, 1]$ is an n -ary Sugeno integral if and only if it is an idempotent weighted linear polynomial function (see [5]), conclusions from [8] can be applied to discrete Sugeno integrals. Since the Sugeno integral is widely recognized as a qualitative aggregation operator whose lattice-based form is well suited for combining heterogeneous and ordinal data, and since the previous observation provides a natural connection between the abstract algebraic framework and this well-known qualitative aggregation tools, further investigation of Sugeno-type aggregation operators is more than justified.

The main aim of this paper is to extend results form [8] to Sugeno-type integrals as aggregation operators within the proposed Ω -group framework. Additionally, since the lattice-valued formulation allows the aggregation process to preserve the inherent imprecision of data while supporting flexible notions of equivalence through the aggregation of weak congruences, possible application in digital forensics [3,6] is being considered.

Acknowledgement: This research was supported by the Science Fund of the Republic of Serbia, Grant no 6565, Advanced Techniques of Mathematical Aggre-

gation and Approximative Equations Solving in Digital Operational Research-AT-MATADOR.

References

1. Ardanza-Trevijano, S., Chasco, M.J., Elorza, J., de Natividade, M., Talavera, F.J. Aggregation of T-subgroups, *Fuzzy Sets and Systems* **463**, 108390 (2023)
2. Bejines, C., Chasco, M.J., Elorza, J. Aggregation of fuzzy subgroups, *Fuzzy Sets and Systems* **418**, 170–184 (2021)
3. Borzová, J., Hutník, O., Kleinová, M. Chain-based Sugeno-like operators: A new take on the Sugeno integral as a scientometric tool, *Fuzzy Sets and Systems* **521**, 109578 (2025)
4. Halaš, R., Pócs, J., Pócsová, J. Remarks on Sugeno integrals on bounded lattices, *Mathematics* **10**, 3078 (2022)
5. Marichal, J.-L. Weighted lattice polynomials, *Discrete Mathematics* **309**, 814–820 (2009)
6. Stoffel, K., Cotofrei, P., Han, D. Fuzzy methods for forensic data analysis. In: Proc. Int. Conf. on Soft Computing and Pattern Recognition (SOCPAR 2010), pp. 23–28. IEEE, Cergy-Pontoise (2010)
7. Šešelja, B., Tepavčević, A. Ω -group in the language of Ω -groupoids, *Fuzzy Sets and Systems* **397**, 152–167 (2019)
8. Štajner-Papuga, I., Tepavčević, A. On aggregations of algebraic objects in data modeling, *Mathematics* **14**, 570 (2026)
9. Talavera, F.J., Ardanza-Trevijano, S., Bragard, J., Elorza, J. Aggregation of T-subgroups of groups whose subgroup lattice is a chain, *Fuzzy Sets and Systems* **473**, 108717 (2023)

Author Index

- Abdulgafer, Abdullah, 2
Al-Muhtaseb, Woorod, 2
Ammar, Nour, 29
Aragón, Roberto G., 19
- Borrego-Díaz, Joaquín, 17
- Castro, Javier, 15
 Chacón-Gómez, Fernando, 40
 Chen-Abolacio, Adam Leiyi, 17
 Cordero, Pablo, 44
 Cornejo, M. Eugenia, 23, 36, 40, 42
 Costantini, Stefania, 38
- Enciso, Manuel, 44
 Esteva, Francesc, 36
- Fariñas del Cerro, Luis, 36
 Fernández-Mora, Arturo, 31
 Fiala, Karel, 34
- Godo, Lluís, 36
 Gómez, Daniel, 15
 Gutiérrez, Inmaculada, 15
- Hatwagner, Miklós F., 10, 12
 Hegedűs, József, 10
 Hrivová, Ivona, 47
- Jočić, Dragan, 57
- Kalafut, Juraĵ, 47
 Kalina, Martin, 47
 Kaszás, András, 27
 Kóczy, László T., 10, 12, 27, 29, 53
 Kowalski, Piotr, 8
- Lobo, David, 23, 24
- López-Gómez, Julio Alberto, 4, 6
 López-Molina, Pablo, 24
 López-Rodríguez, Domingo, 21
- Martínez, Luis, 31
 Medina, Jesús, 19, 23, 36, 40, 42
 Mesiarová-Zeménková, Andrea, 47
 Molina-Ruiz, Samuel, 19
 Montoro-Montarroso, Andrés, 2
 Mora, Ángel, 21, 44
 Moreno-García, Juan, 4, 6, 31
 Muñoz-Valero, David, 4, 6, 31
 Murinova, Petra, 34
- Nagy, Szilvia, 55
 Novák, Vilém, 34
- Ocaña-Alcázar, Francisco J., 42
 Ojeda-Hernández, Manuel, 21
 Olivas, José A., 2
- Pérez-Gámez, Francisco, 44
 Pérez-Sechi, Carlos I., 15
 Pitoni, Valentina, 38
 Plaza, Guadalupe, 2
 Pomezanski, Vanda O., 27
 Precup, Radu-Emil, 26
- Romero, Francisco P., 2
- Sebestyén, Barbara, 12
 Serrano-Guerrero, Jesús, 2
 Shen, Qiang, 14
 Štajner-Papuga, Ivana, 57, 59
 Stepanović, Vanja, 49, 51
 Sziová, Brigita, 55
- Tepavčević, Andreja, 49, 51, 59

Trkulja, Aleksandar, 51
Tüü-Szabó, Boldizsár, 53

Várkonyi-Kóczy, Annamária R., 46

Villarrubia-Martín, Enrique Adrián, 4, 6
Vozna, Alina, 38

Yao, Yiyu, 1